

Smarter Connected Home, Commercial Systems & Cellular Solutions



### **Table of Contents**

Napco Commercial Firewolf Fire System Solutions	1
Napco Commercial Firewolf Fire Panels, Addressable, Commercial Wireless & Conventional Fire Options	
Configuration Diagram, Fire Systems	2
Configuration Diagram, Fire Systems StarLink Fire & Merchantile Fire & Burglary Communications	4
Napco Commercial Integrated Systems, Fire, Burglary & Access, Addressable, Commercial Wireless & Conventional Options:	5,6
Configuration Diagram, Commercial Integrated Systems	5
iBridge Connected Home & Introduction to Dealer Program	
iBridge Connected Home Services & Benefits	
iBridge Messenger SMS/MMS Notifications & Video Alerts	
Napco Remote Service Apps	
StarLink Universal Radios, CDMA,GSM & NetLink Internet Communication Options	
iSee Video Remote Video, Standalone or Integrated with iBridge	
Reference Matrix, iSee Video Cameras & Options	
iRemote Virtual Keypad App	
Keypads & User Interfaces	
Gemini Security Panels with Control4 System Integration	
Gemini Security Systems, Panels & Peripherals	
Gemini Wireless Devices & Receivers	
Configuration Diagram, Building a Gemini System	
StarLink Cellular Solutions Overview	
Firewolf Conventional Fire/ Lifesafety Devices	
Napco Motion Sensors (wired)	
Gemini Access Control & Enduser Management	
Gemini Wireless Carbon Monoxide Detector	
Reference Matrix, Gemini Panel Line, Features & Accessories	
Napco Security Technologies Commercial & Government Solutions	
Napco Security Technologies & Its Divisions	

#### Napco StarLink Cellular Solutions, Now Expanded by Popular Demand!



# Napco Commercial Firewolf Series:

Robust, flexible 24V commercial fire systems supporting up to 255 zones/points using all-new fire devices in hardwire, wireless, conventional & addressable technologies

GEM-C Firewolf Series 24V Commercial Intelligent Analog Addressable Fire Panels, NFPA72-

compliant, 96 outputs, 4 onboard NACs (6.5A total), expandable to 24, built in Sync/Strobe/Horn Module (System Sensor & Wheelock) and dual line DACT plus optional TCP/IP reporting.Powerful battery capacity up to 32Ah total. More addressable devices than any in its class; mile-long loop lengths and more device load each. Cost-effective retrofits -supports conventional legacy devices & existing wiring (all types/gauges). Comprehensive local and remote programming & diagnostics. Printable AHJ reports of analog device sensitivity settings with current readings (uploadable)

- More zones/points up to 255
- More power 7 amps
- More NACs 4 on board (expandable to 24)
- Onboard strobe/horn sync
- More standby power
- 32 Amp hour battery capacity
- Regulated 24V output

#### Regulated Auxiliary Power Supply Commercial fire, 12V regulated 2A model

Firewolf Advanced Analog Addressable Commercial Fire Devices support auto-drift compensation and maintenance alert function

UL Commercial Grade Gemini Wireless Devices with supervised tamper & automatic, continuously supervised signal strength (requires no manual test activation).

#### Firewolf Menu-Driven Custom Alpha Annunciators Same familiar Napco

EZ-programming and usage. (Keyswitch support, too.) Customizable Quick-Start Preset Program & Auto-Learn of SLC Devices.

#### Code-compliant Integrated Security & Access

Control Option Pre-Isolated Circuits & Power Customizable Quick-Start Preset Program & Auto-Learn of SLC Devices & Modular Access Control option. (Reference Models GEMC-BM/PS or -BSLC & GEM-ACM1D / -2D.)

#### New! StarLink Universal Sole Path Fire Cellular Communicators

Work with virtually any 12V-24V FACP. Choice of

CDMA and GSM 3/4G Models, meet or exceed today's codes, UL864 and NFPA72 2013, etc.

Firewolf

tarl ink

NAC Extender provides nearly 7A and 4 onboard NACs with up to 2A ea; up to 24V 16Ah total battery capacity. Easily distributes synced bell and strobe outputs with built in module. Supervised and bus-activated with no separate modules or programming required. Monitors AC, battery trouble, tamper and ground fault on Napco bus or provides universal FACP support. 3 Programmable relay outputs; 2 low voltage; 1 high-voltage 12OV rated relay.

*Compliances* - NFPA 72, UL Commercial Fire, UL864 9th Ed., UL985, CSFM and NYC Fire Department Certifications.



# Firewolf Fire Panels: Addressable, Commercial Wireless &



#### Firewolf<sup>™</sup> Series

Intelligent features, cost-effective design and rigorous code compliance

#### Features:

- Analog, Addressable, Conventional, Wireless &/or Hardwired technologies
- Wireless Fire Full line of UL Commercial Grade long-range supervised models
- More Addressable Devices than any in its class; mile-long loop lenghts and more device load ea. ch. Supports 10,000 Feet of SLC Cable!
- Fire Quick-Start System Programming & EZ-Maintenance Modes
- More value and power on-board for a more cost-effective solution -
  - Built in DACT (TCP/IP option), Horn/Strobe Sync. (Wheelock/System Sensor protocol), 4 programmable NACs (up to 24), 7A power, regulated 24V output
- Cost-effective retrofits -supports conventional legacy devices & existing wiring (all types/gauges)
- Comprehensive local and remote programming & diagnostics.
- Quick Smoke Obscuration Reports for AHJs (Printable reports of analog device) sensitivity settings with current readings (uploadable) Optional NAC Extender for universal FACP support and Regulated Power
- Supplies, too
- Code-compliant integrated Security System option with independent preisolated circuits
- Compliances NFPA 72, UL Commercial Fire, UL864 9th Ed., UL985, CSFM and NYCFD

Napco Commercial Firewolf Fire System Kit Configurations: Napco Commercial Firewolf 255pt 24V Intelligent Addressable **Commercial Fire System Kit** 

#### GEMC-FW-255KT

122212

- 24V Panel, 255 pts via commercial addressable, wireless or conventional fire devices, 4 on onboard v NACs providing up to 6.5A notification power
- 7Amp, 24V Power Supply
- Built in horn strobe sync on each NAC (Wheelock/System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports; optional TCP/IP
- Fire Quick-Start System Programming & EZ-Maintenance Modes; Quickloader up/downloading incldg Quick access, Smoke Obscuration Reports, Automatic drift compensation for smoke detectors too
- Nearly a mile max. wiring run any wire type ideal for retrofits. 24V and 12V legacy devices supported
- Large red locking enclosure, flush or surface mount. Up to 32AH battery capacity.
- Includes Fire Annunciator (GEMC-FK1) LCD display, menu-driven, mounts anywhere on bus. (Also global Annunciator unlock feature & full keyswitch support).

# **Conventional Fire Options**



#### Napco Commercial Firewolf 128pt 24V Intelligent Addressable Commercial Fire System Kit GEMC-FW-128KT

24V Panel, 128 pts via commercial addressable, wireless or conventional fire devices, 4 on onboard programmable programmable NACs providing up to 6.5A notification power.

- 7Amp, 24V Power Supply
- Built in horn strobe sync on ea. NAC
- Built in dual line communicator; dual onboard serial ports; optional TCP/IP
- New Fire Quick-Start System Programming & EZ-Maintenance Modes; Quickloader up/downloading including Quick access, Smoke Obscuration Reports; Automatic drift compensation for smoke detectors too
- Nearly a mile max. wiring run any wire type ideal for retrofits.
- Supports 24V and legacy 12V devices
- Large red locking enclosure, flush or surface mount. Up to 32AH battery capacity
- Includes Fire Annunciator (GEMC-FK1) LCD display, menu-driven, mounts anywhere on bus (Also, global Annunciator unlock feature & full keyswitch support.)

#### Napco Commercial Firewolf 32pt 24V Intelligent Addressable **Commercial Fire System Kit GEMC-FW-32KT**

- 24V Panel, 32 pts via commercial addressable, wireless or conventional fire devices, 2 on onboard NACs providing up to 4A notification power.
- Locking medium red enclosure (flush or surface mount). Houses up to 16AH battery backup.
- 7Amp, 24V Power Supply
- Built in horn strobe synch module on ea. programmable NAC
- Built in dual line communicator; dual onboard serial ports; optional TCP/IP
- New Fire Quick-Start System Programming & EZ-Maintenance Modes; Quickloader up/downloading incldg Quick access, Smoke Obscuration Reports, Automatic drift compensation for smoke detectors too
- Nearly a mile max. wiring run any wire type ideal for retrofits. 24V and 12V legacy devices supported.
- Includes Fire Annunciator (GEMC-FK1) LCD display, menu-driven, mounts anywhere on bus (Also, full keyswitch support.)

#### Napco Commercial Firewolf 32pt Conventional Fire System Kit -Ideal for sprinkler/waterflow **GEMC-FW-32KT**

#### **GEMC-FW32CONVKT**

- 24V Panel, 32 Points via commercial addressable, wireless or conventional fire devices, 2 onboard programmable NACs providing up to 4A notification power
- Locking, Medium Red Enclosure, 16 x 17" door, with 14.25" x 16" base (flush or surface mount). Houses up to 16Ah battery backup.
- 4 Amp, 24V Power Supply
- Conventional 8-zone 2-wire fire input module, for conventional 2-wire smokes or any conventional fire detection device (GEMC-F8ZCPIM)
- Built in horn/strobe synch. module on each NAC (Wheelock/System) Sensor protocol)
- Built in dual line communicator; dual onboard serial ports
- New Fire Quick-Start System Programming & EZ-Maintenance Modes; Quickloader up/downloading
- Menu-driven LCD Fire Annunciator mounts anywhere on bus (GEMC-FK1)



#### 7Amp NAC Extender for Universal FACP use or with GEMC / Firewolf Systems **GEMC-NAC7S**

7 Amps of Power for use with NAPCO or other FACP panel brands

• 4 onboard programmable NACs with up to 2A ea. expandable up to 24 per system

Regulates 24V auxiliary power

- Distributes synched bell and strobe outputs with built-in module
- Monitors AC, battery trouble, tamper and ground fault on Napco bus or provides universal FACP support
- Red locking enclosure, accommodates up to 16Ah total battery capacity

#### 12VDC Fire Power Supply for GEMC / Firewolf and Gemini Panels GEMC-12V2ASP-CF 12VDC

- Power Supply for Fire Bus of Firewolf & GEMC Napco Commercial Panels, remote supervised
- Direct 120VAC connection
- Supports 2ea. 12V,7Ah standby batteries

#### Wireless, UL Commercial, Fire Peripherals

GEMC-REVC Wireless 255 point RF Receiver (4/system, max.) GEMC-WL-SMK Wireless Smoke, Photoelectric (complete) GEMC-WL-HEAT Wireless Heat, 135° F

GEMC-WL-WD Wireless 1-pt input module

GEMC-WL-WD2 Wireless Input module (converts any UL device into a wireless device, ex. pull stations or sprinkler supervisories.)

GEMC-WL-CO Wireless Carbon Monoxide Detector (For complete info see pg 27)



Conventional Fire System Peripherals GEMC-FK1 LCD Fire Red Annunciator (Menu-driven operation, functionality for Reset, Acknowledge, Silence (with disable).

GEMC-F82CPIM Conventional 8-zone 2-wire fire input module. Plugs into motherboard, for conventional 2-wire smoke detectors or any conventional fire detection device. GEMC-EZM8 8-point Expansion Module

FWC-CNV-PULL Conventional Single Action Pull Station, with Hex Reset FWC-CNV-PULLK Conventional Single Action Pull Station, with Key Reset FWC-CNV-PULL2 Conventional Dual Action Pull Station, with Hex Reset FWC-CNV-PULL2K Conventional Dual Action Pull Station, with Key Reset erals

GEMC-WL-SMK Gemini Commercial Wireless Smoke, Photoelectric (complete).

GEMC-WL-HEAT Gemini Commercial Wireless Heat, 135° F GEMC-WL-WD2 Gemini Commel Wireless Input Module converts any UL listed device into a UL wireless device (ex., pull stations or sprinkler supervisories.)

GEMC-REVC Gemini Commercial Wireless 255 point RF Receiver (up to 4 per system, max.) GEMC-WL-CO Wireless Carbon Monoxide Detector Addressable Firewolf Peripherals

GEMC-FW-SLC Addressable SLC Fire Module, supports up to 128 addressable SLC fire

Gemc-Fw-Stc-SMK Addressable SLC Pite Module, supports up to 128 addressable SLC line devices, below. Up to 2 connect to Panel. FWC-FSLC-SMK Addressable Analog SLC Smoke, photoelectric, head\*\* FWC-FSLC-HEAT Addressable SLC Duct smoke detector, photoelectric (Requires use of GEMC-24VR Voltage Regulator) Inclds 2 onboard relays that follow state of detector. FWC-FSLC-DUCTRA Remote Indicator Plate with LED indicator & key reset. FWC-FSLC-ETM2 Addressable SLC 2-zone conventional expansion module. Lices one

FWC-FSLC-EZM2 Addressable SLC 2-zone conventional expansion module. Uses one address on SLC loop, but yields 2 indep. contact monitoring circuits, for pull stations, water flow and other dry contact alarm initiating devices.

FWC-FSLC-EZM1 Addressable SLC 1-input conventional module, similar to usage above. FWC-FSLC-CZM Addressable SLC Conventional Zone module, for montoring of dry contacts, ie., pull stations and conv. smokes (Requires use of GEMC-24VR Voltage Regulator) Creates a 24V 2-wire fire zone on the SLC loop, selectable Class A or B zone

wiring. FWC-FSLC-RM2 Addressable SLC 2-output module (requires 2 SLC addresses) FWC-FSLC-ISO Addressable SLC Short Circuit Module (Optional: For special applications,

meets Class A, Style 7 loop reqts.) FWC-FSLC-SOM1 Addressable SLC Fire supervised output module. Application examples: elevator recall, HVAC shutdown, add'l NAC output w/ power supply

(Requires use of GEMC-24VR Voltage Regulator) FWC-FSLC-PULL Addressable SLC Fire Pull Station, standard hex-key reset.

FWC-FSLC-PULLK Addressable SLC Fire Pull Station, with key reset.

FWC-FSLC-PULL2 Dual action, pull station with hex-key reset. FWC-FSLC-PULL2K Dual action pull station, with key reset.

FWC-FSLC-PROG2 Tool for address-programming SLC devices FWC-FSLC-SMK6B \*\* Smoke/Heat 6'' Base, required for FWC-FSLC- SMK and -HEAT devices

**GEMC-NAC7S Remote 4-output NAC Extender**, for 6.5A ttl, or 2A, max. on any 1 output. Red 14 x 16" can, connects to 120VAC, supports 24V 16Ah standby batts. Supervised, fire bus connection. System Sensor and Wheelock NAC sync. (5/system, for 20

Supervised, fire bus connection. System Sensor and Wheelock NAC sync. (5/system, for 20 add'I NAC circuits ttl.). 3 Programmable relay outputs; 2 low voltage: 1 high-voltage 120V rated relay. GEMC-12V2APS-CF 12VDC Power Supply for Fire Bus, remote supervised. Direct 120VAC connection, supports 2ea. 12V, 7Ah to 16Ah standby batts. GEMC-FRINT Parallel Printer Module GEMC-RM3008 8 Form C Relay Output Module GEMC-R3232 RS232 Adapter for serial output from Panel GEMC-R128 PGM Output Module 8 one collector PGM outputs.

GEMC-OUT8 PGM Output Module, 8 open collector PGM outputs

GEMC-NL-MOD Internet Reporting Module SLE-CDMA-FIRE StarLink Universal Sole Path Fire Cellular Communicator, CDMA (see next page) SLE-GSM-FIRE StarLink Universal Sole Path Fire Cellular Communicator GSM (see next

page)

3



# Starlink Sole Path Fire Communicators & Merchantile Commercial Fire or Burglary Models



StarLink Sole Path Cellular Communication Options, UL & NFPA Code Compliant

#### Napco StarLink3 Universal Sole Path Fire Cellular Communicator

- Universal CDMA or GSM Network full event cellular reporting from any panel brand, virtually anywhere.
- For use with all 12V-24V control panels and FACPs that communicate using Contact ID/4/2
- Easiest 4-Wire Installation & Activation Just Enter a Radio ID, Dialer Capture completes all ( no entering phones nos., formats, account nos.)
- Reports to any Central Station via GSM 3/4G or CDMA (Verizon Network Certified) Models SLE-GSM-FIRE & SLE-CDMA-FIRE, respectively
- Bonus: Full High-Speed Napco Panel remote uploading/ downloading (Requires cable \*\*)
- Takeover Feature Easily captures any panel's existing CS phone number and allows rerouting to another central station without going to the panel
- Easy Online Account Management Choice of affordable subscriber service plans, separately available at www.napcocomnet.com
- UL Listed. Meets or exceeds code: NFPA72 Editions: 2013, 2010, 2007; UL 864, 9th Ed., UL1610, UL985, UL1023, UL1635

Choose SLE-CDMA-FIRE for reporting CDMA, Verizon Network Certified . Or, SLE-GSM-FIRE for reporting on GSM 3G/4G Cellular Network.

#### SPECIFICATIONS

- Dimensions: 5-3/8"x 7-7/8"x 1-7/8" (HxWxD)
- Weight: 13.5 oz.
- Three hardwire trigger inputs
- Three PGM outputs, open collector, 3V (active), 50 mA (idle)
- Operating Temperature: 0 to 49°C
- 12V 24V Universal FACP Support

#### **AVAILABLE OPTIONS:**

SLE-DLCBL Gemini Up/Downloading Cable for Napco Panels only

 $\ensuremath{\text{SLE-DLEXT}}$  Optional, as above, for downloading, extends distance to Napco panel up to 100'

**SLE-SMTCHG** Optional Smart Charge Module overcomes limitations of AC access or standby power. (Uses 4AH/12V Rechargable Battery)

#### StarLink Merchantile Commercial Fire or Burglary Models in metal enclosure

 Same reporting options as StarLink, at left, but in UL Merchantile metal enclosure with option for Power Supply in GSM or CDMA versions.

Merchantile Model SLECDMA-CFB, shown available with provision for battery backup - or - with power supply, Model SLECDMA-CFB-PS

#### FIRE MODELS:

**SLE3/4G-CFB-PS** Commercial Fire/ Burglary, 3G/4G, red enclosure with 120V Hardwired Power Supply

**SLE3/4G-CFB** Commercial Fire/ Burglary, 3G/4G, red enclosure,no power supply

SLECDMA-CFB-PS Commercial Fire/ Burglary, CDMA, red enclosure with 12OV Hardwired Power Supply

SLECDMA-CFB Commercial Fire/ Burglary, CDMA, red enclosure, no power supply

#### BURLARY MODELS (not shown):

**SLE3/4G-CB-TF** Commercial Burglary, 3G/4G, white enclosure with Plug in transformer

SLE3/4G-FB Commercial Burglary, 3G/4G, white enclosure, no power supply

**SLECDMA-CB-TF** Commercial Burglary, CDMA, white enclosure with Plug in transformer

**SLECDMA-CB** Commercial Burglary, CDMA, white enclosure, no power supply







### Napco Commercial Platform: GEMC Fire & Burglary Integrated System Configuration Diagram



#### Napco Commercial System Kits: GEMC-Integrated 255KT 255 Point GEM-C Commercial Integrated. Fire/Burg System Kit

- 24V Panel, 255 Points via commercial addressable, wireless or conventional fire or burg. devices, 4 on board NACs, 8 partitions (No Loop Isolator/Extender required)
- 7 Amp, 24V Power Supply
- Burg. Module, with power supply with built in bus isolator for complete separation of fire and burg power and battery standby operation (GEMC-BM/PS)
- Built in horn/strobe synch. module on each NAC (Wheelock & System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports
- Quickloader up/downloading including remote smoke obscuration reporting
- Locking, Large Red Enclosure, 16 x 25" reversible door, with 14.25" x 25" base (flush or surface mount.) Houses up to 32Ah battery backup.
- Menu-driven LCD Fire Annunciator (GEMC-FK1) mounts anywhere on bus (Also, full keyswitch support)

#### GEMC-Integrated 128KT 128 Point GEM-C Commercial Integrated. Fire/Burg System Kit

- 24V Panel, 128 Points via commercial addressable, wireless or conventional fire or burg. devices, 4 on board NACs, 8 partitions (No Loop Isolator/Extender required)

- 7 Amp, 24V Power Supply
- Burg. Module, with power supply with built in bus isolator for complete separation of fire and burg power and battery standby operation (GEMC-BM/PS)
- Built in horn/strobe synch. module on each NAC (Wheelock & System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports
- Quickloader up/downloading including remote smoke obscuration reporting
- Locking, Large Red Enclosure, 16 x 25" reversible door, with 14.25" x 25" base (flush or surface mount.). Houses up to 32Ah battery backup.
- Menu-driven LCD Fire Annunciator(GEMC-FK1) mounts anywhere on bus (Also, full keyswitch support)

# Napco Commercial<sup>™</sup> GEMC Integrated. Fire/Burglary and



#### GEMC-Integrated 32KT 32 Point GEM-C Commercial Integrated. Fire/Burg System Kit

 24V Panel, 32 Points via commercial addressable, wireless or conventional fire or burg. devices, 2 on board NACs, 8 partitions (No Loop Isolator/Extender required)

- 7 Amp, 24V Power Supply
- Burg. Module, with power supply with built in bus isolator for complete separation of fire and burg power and battery standby operation (GEMC-BM/PS)
- Built in horn/strobe synch. module on each NAC (Wheelock & System Sensor protocol)
- Built in dual line communicator; dual onboard serial ports
- Quickloader up/downloading including remote smoke obscuration reporting
- Locking, Large Red Enclosure, 16 x 25" reversible door, with 14.25" x 25" base (flush or surface mount.). Houses up to 32Ah battery backup.
- Menu-driven LCD Fire Annunciator (GEMC-FK1) mounts anywhere on bus (Also, full keyswitch support)



 24V Panel, 96 Points via commercial addressable, wireless or conventional burg. devices, 7 partitions

- Locking, Medium White Enclosure, 16 x 17" door, with 14.25" x 16" base (flush or surface mount.). Houses up to 16Ah battery backup.
- 4 Amp, 24V Power Supply
- Addressable SLC Burg Module, supports up to 96 addressable SLC burg devices (GEMC-BSLC)
- Built in dual line communicator; dual onboard serial ports
- Quickloader up/downloading
- Menu-driven LCD Burglary Keypad with built-in 4 zone EZM, mounts anywhere on bus (GEMC-BK1)

#### 12VDC Burglary Power Supply for GEMC and Gemini Panels

#### GEMC-12V2PS-R 12VDC

- Power Supply for Burg. Bus of GEMC Panels, remote supervised.
- Powered by supplied 16.5V, 50VA plug-in transformer, (Note: Housing is white in
- Supports 2ea. 12V, 7Ah standby batteries.
- Backward compatible with all standard Gemini Panels, too.
- Alarm Panel supervised power option

Note: Also available, Fire Bus Model with Direct 120VAC connection, model GEMC-12V2ASP-CF 12VDC

#### Napco Commercial Access Control Option for GEMC and Gemini Panels

GEMC-ACM1D Access Control Module with power supply in enclosure GEM-2D 2nd Door Plug-In Module for use with ACM1D

#### **Burglary & Fire Accessories & Options:**

Wireless, UL Commercial, Peripherals GEMC-REVC Wireless 255 point RF Receiver (4/system, max.) GEMC-WL-SMK Wireless Smoke, Photoelectric



GEMC-WL-HEAT Wireless Heat, 135° F GEMC-WL-WD Wireless 1-pt input module GEMC-WL-WD2 Wireless 2-input module GEMC-WL-PIR Wireless 50' PIR GEMC-WL-DT Wireless 40' Dual Tech'y microwave/PIR GEMC-WL-GB Wireless Glassbreak

#### Wireless Gemini Commercial Carbon Monoxide Detector

GEMC-WL-CO, is a high-quality carbon monoxide (CO) detector with built-in supervised, digitally coded wireless transmitter and visual and audible alarm and low battery indicators. Designed for detection accuracy and reliability, it's part of both the Gemini and Gemini Commercial Grade wireless lines, and supported by Napco's GEM-RECV and Commercial GEMC-RECV Series Supervised Receivers, as part of GEMINI,



GEMC & Firewolf Alarm Systems. This compact, white detector, with 5-3/8 diameter and 2" profile, uses a 3V Lithium Battery (CR123A) for long dependable product life. It will monitor alarms, restores, low battery, tamper and status, and is designed to meet or exceed today's rigorous life safety compliances, including testing to sensitivity limits specified in UL 2075, UL 2034.

#### **Commercial Burglary Accessories and Options**

**GEMC-BM/PS** Burg Module with 12V power supply provides isolated 4-wire burg bus for burg keypads and devices, plus 12V power output for aux. devices. Independent Burg. Bell output. Complete separation of fire and burg power, plus indep. burg. battery connection and charger for indep. burg. standby operation in power failure.

**GEMC-BM** Burg Module, isolated 4-wire burg bus for burg keypads and devices, plus 12V power output for aux devices. Indep. Burg bell output.

**GEMC-BSLC** Addressable SLC Burg Module, supports up to 128 addressable SLC burg devices. Up to 2 connect to GEM-C panel.

#### **Burglary Peripherals**

**GEMC-BK1 LCD** Burglary Keypad for Integrated. System, with 4-zone EZM built in (Requires GEMC-BM or BM/PS Module.)

GEMC-BSLC-4PT Addressable SLC 4 point input expansion module

GEMC-BSLC-1PT Addressable SLC 1 point input expansion module

GEMC-BSLC-DT Addressable SLC Commercial Dual Tech Microwave/PIR, 40  $\times$  40'

GEMC-BSLC-PIR Addressable SLC Commercial PIR, 50 x 50'

GEMC-BSLC-RLY Addressable SLC Commercial 1 point output module

**GEMC-KOTamperKT** Merchantile Tamper Kit, for large panel enclosures, supervised. (Not necessary if housing is recess-mounted.)

6



color not as shown )

# iBridge Connected Home & Security.

Smart. Simple. More Affordable.





# Protect Your Home Turf and Cash in On \$71B Connected Home Market.



The time is now to maximize accounts & account value! Expand your business into the connected home market today for new business, growth and RMR.

We'll provide everything you need, and show you how, as part of the iBridge Connected Home Dealer Program.

#### Connected Home Made Easy with the iBridge Program

Combine security, video, lighting, locking, and climate control services, using free iBridge App, on accounts smartphones / tablets. Lower equipment costs, using just one iBridge ZREMOTE Module, providing both remote services and z-wave control, plus 12-mos. account service. Start leveraging all the media headlines & national ad campaigns large competitors are attracting your customers with. We'll give you the training,



marketing materials and know-how to increase your accounts, value and retention with the stickier, smarthome/security services today's consumers want.

iBridge Connected Home Dealer Program has All You Need:

- Leading Edge Product & Free Smart Phone Apps
- New iBridge Messenger Notifications via SMS Text or MMS Live Video Alerts
- Preferred Pricing
- Certified Trainings: Sales, IP 101 & Technical
- Free Custom Marketing Materials & Co-op Advtg
- Exclusive Consumer Website & Leads
- Tech Support & Customer Service Hotlines
- Annual Event



### iBridge Connected Home & Security. Smart. Simple. More Affordable.

Jones Hom Security System Ala



#### FOR YOUR CUSTOMERS



Now it's easy and affordable for your customers to add remote control of their security system by taking advantage of iBridge Connected Home Services and Messenger SMS/MMS Notifications



Your customers can easily check up on their home, their loved ones and valuables, and see what's actually happening in the event of an alarm with live MMS Video alerts



Control thermostats automatically, and onthe-go with iBridge's easy to use mobile app, your customers can always come home to a comfortable environment



Have your customers take control of their energy use by controlling their lights automatically and on-the-go



Now your customers don't have to worry if they left the door unlocked or the garage door open. They can have complete remote control over all the entry points to their home



Once programmed your customers can remotely control their appliances using the iBridge system with their smart phone or tablet



Your customers can program different lighting and thermostat settings to have them set exactly how they want them with their changing moods











#### FOR YOUR BUSINESS

# PREFERRED PRICING

Become part of the iBridge Connected Home Dealer Program, and take advantage of this rapidly growing, RMR-building category of services and all these benefits, many exclusive to Authorized Dealers

LEAD GENERATING WEBSITE

Dealer Program Members get qualified leads targeted specifically within your own local market by using Google Adwords/PPC to connect potential buyers directly with your company and company website, increase image and exposure

TRAVEL-LESS SERVICE VIA APP

Set up & update systems right from your smart device for No-Roll™ service calls with iBridge! Advanced Scenes and Schedules, once only for high-end homes – Now made easy and affordable

RARKETING & COOP PROGRAM

We'll provide a Turn-Key assortment of Members-Only marketing materials customized for your company- All you need to get started is your completed contract, a high-resolution electronic logo and contact info

### FREE TRAINING

We'll train you and your team when you need it, and where you need it, nationwide



iBridge Connected Home Dealer Program Members can use Members-Only customer service & Tech Support hotlines for speedy care when you need it

### With iBridge Messenger SMS/MMS Service, Your Accounts Know All & See All...



If there's an alarm in progress, get a text message, and a video clip to click on, to see what's going on



Know when the pool gate is opened, while no one should be there. See who is, with a click right in the message....



Set worries aside, knowing, even seeing for yourself, dad took his meds on time, or the kids came home from school safe and sound, and get notified with a text, if they didn't.



- SMS and/or MMS Text Notifications with Video Alerts

   Reminders, Confirmations & Exceptions. Supports all
   phone types
- Solve any issues they're notified of with iBridge remote Connected Home Services (lock/unlock the door, arm the alarm, adjust HVAC, shut off lights, etc)
- Show what was happening, both before and after the alarm or event, with Live Video Alerts incldg 10-Sec.
   Pre-and Post-Event Video Clips. Go-Live option, too.
- Broadband-based, Multimedia Technology for Hi-Res 20FPS VGA Live Video delivered right on their mobile devices (w/o logging in elsewhere)
- Consumers Easily Select & Customize the Notifications they Want & Who Gets Them
- More Intelligent EZ Messages-Created from any system activity on the panel bus:
- Zone, or group of triggers, time, user, alarm, event or grouped events, in easy terms, e.g, door unlocked, security system disarmed (or not), gun-or liquor-cabinet opened, dispensing meds.(or lack of), kid (name here) returned home, HVAC low temp alert, side pool gate ajar.
- Backward-Compatible. For New & Retrofit Gemini or iBridge Accounts

iBridge Messenger SMS/MMS Notificaions & Reminders is a selectable option for the connected home service on www. napcocomnet.com. (For more see WI2129A or visit &/or for User Manual see WI2117A).

# iBridge Remote Services & Apps:

Grow your business & RMR and prevent attrition





iRemote™ Virtual Keypad Module & App – Anything you can do on a real on-premises keypad you can do remotely, even service calls

- Arm/Disarm
- Bypass, Temp. Control
- Address Programming For gas-free updates/service calls
- Works the same/ looks the same nothing new to learn/teach – control anywhere there's internet access
- Free App on smart device, tablet or PC.
- Dealer-Customized Subscriber Access Site included, Multilingual
- No special central station required

# iRemote



#### StarLink Universal Radios & App

- Starting at under \$100, advanced primary/ backup full data radio works on any panel (Contact ID/4/2), anywhere
- Free App: One-touch remote arm/disarm for customer convenience from anywhere (with status indicator); SMS text/email option
- Programmed out-of-the-box, with 1-step enrollment. No activation fee.
- Takeover Feature to change CS (reports to any)
- Future-Proof, field upgradable for network changes
- Optional Gemini Panel up/downloads in minutes
- Free Sales Aids







### iSee Video™ Remote Video – The Easiest, The First, The Best

- Hi-Res Streaming Video 25FPS @ VGA res. 640x480
- 10-Minute WiFi Camera Installation No Activation Fees; All-inclusive kits w/ 12-mos. Service
- Plug-n-Play Easy Camera Enrollment; Secure WiFi Network
- View Live, Archived or Auto-Email on Events; viewable anywhere there's internet access
- Detail /Quality you can see and zoom-in on!
- 24/7 Recording Option
- Dealer-Customized Subscriber Access Site included, Multilingual
- Free Sales Aids

## iSeeVideo 🔀



#### iBridge<sup>®</sup> Connected Home Services -App & Optional Touchscreen/Tablet

- Control Alarms, Video, Temperature, Lighting & Locking & iBridge Messenger sends SMS/MMS Notifications & Video Alerts
- Turn on/off lights and alarms; lock/unlock doors; set thermostats or set moods or scenes; view local & remote video, get emailed videos.
- Cost-Effective Z-Wave Device Control just using iBridge's affordable bus-mount Z-Wave Module.
- Activate custom scenes based on, schedules or occupancy from tablet or phone
- Napco No-Roll<sup>™</sup> Customer Service Calls Dealers Edit/ Add Z-Wave devices easily, remote-configurable from their own smart devices.
- Bridge App for iPhone/Droid or PC &/or WiFi Touchscreen/Tablet



## StarLink3 Universal CDMA or GSM Radios. Your choice of Panel



#### New! StarLink3<sup>™</sup> Universal CDMA Radio -Verizon<sup>®</sup> Network Certified

#### SLE-CDMA:

- Universal CDMA Network full event reporting from any panel brand, virtually anywhere
- For use with all alarm panels that communicate using Contact ID/4/2
- Easiest 4-Wire Installation & Activation with Dialer Capture
- Reports to any Central. NO special equipment. NO radio activation fee.
- Smart Phone App for Customer Remote Arm/Disarm and enhanced EZ One-Wire Gemini Panel-Connect (see SLE-DLCBL below)
- Takeover Feature Easily captures any panel's existing CS phone number and allows you to reroute it
- Primary or Backup Alarm Communications
- Unbeatable Cost-Saver Upgrade Incentive & Low Service Plan Rates
- UL Listed; Verizon Network Certified



#### StarLink3 Universal 3G/4G GSM Radio

#### SLe-GSM-3/4G:

- Full event 3G/4G GSM wireless reporting from any panel brand, virtually anywhere
- Same Great Performance, New Look
- For use with all alarm panels that communicate using Contact ID/4/2
- Easiest 4-Wire Installation & Activation with Dialer Capture
- Reports to any Central. NO special equipment. NO radio activation fee.
- Smart Phone App for Customer Remote Arm/Disarm and enhanced EZ One-Wire Gemini Panel-Connect (requires SLE-DLCBL below)
- Takeover Feature Easily captures any panel's existing CS phone number and allows you to reroute it
- Primary or Backup Alarm Communications
- Unbeatable Cost-Saver Upgrade Incentive & Low Service Plan Rates
- UL Listed



### Brands, Central Stations & Now Wireless Networks.



#### STARLINK ORDERING INFORMATION:

**SLE-GSM-3/4G:** 3G/4G Network Compatible GSM Universal Wireless Alarm Communicator, SIM card. UL Listed. Service plan(s) sold separately. No Activation Fee.

**SLE-CDMA**: CDMA Network Universal Wireless Alarm Communicator, Verizon Network Certified, UL Listed. Service plan(s) sold separately. No Activation Fee.

**SLE-DLCBL:** For use with Gemini Panels only, Napco Up/download cable, sold separately. Can also be used to plug into panel serial port for one-wire connection, when using on/off App.

**SLE-REMOTE:** Remote App for arming, disarming panel via wireless radio. (Requires service upgrade).

**SLE-DLEXT**: Optional, for up/downloading, extends distance from radio to panel, from 10', up to 100 ft.

**A606:** Free Trifold Enduser Brochure for new and existing accounts. Statement Stuffer or Self-Mailer



**SLE-SMTCHG:** Optional, Smart Charge Module. Allows for optimal radio position regardless of available AC outlets. Also ideal where auxiliary (fire) standby power is too low - without requiring a separate power supply. Uses standard 4AH/12V rechargeable battery.

**SLE-GSMET:** GSM Communicator in metal housing (also accommodates 4 Ah /12V rechargeable battery), SIM card included.

By Popular Demand, Extended StarLink Series, Now includes Fire Cellular Communicators & Merchantile Fire & Burglary Models, see page 4



### NetLink<sup>™</sup> Alternative Alarm Reporting & VoIP Solution

#### NetLink Panel Modules

#### NL-MOD ,GEMC-NL-MOD & NET-COMM

- Communicate alarms via Internet or intranet over a TCP/IP-based network using dynamic IP addressing
- Secure transmissions over the Internet using AES128bit encryption
- Use for primary and/or backup reporting
- NL-MOD NetLink Module can be used with any Napco panel, from the GEMP816 to the X255 and Gemini-Commercial (specify model GEMC-NLMOD when ordering for Napco Commercial Systems) to securely communicate alarms, status, supervisories, etc, pinopointed by-zone
- NET-COMM Economy NetLink Module, is similar, and this less expensive communicator is driven directly by the alarm panel. It supports 5 channel reporting codes, communicating, for example, alarms, panics, fire, telco failure, low battery, etc.

NetLink Receiver for UL Central Station applications: NL-RCV-RMPCUL

- Both NetLink modules report via TCP/IP to any central station or intranet facility with the NetLink UL Listed Receiver (model NL-RCV-RMPCUL)
- UL864/UL1610-listed advanced, rack-mounted receiver
- Interfaces with the conventional Central Station automation system
- 2 Reception Modes: Automatic Mode, where alarm signals are sent normally to the automation system for processing -or- Manual Mode, used when direct operator interaction is desired, using the built in menu-driven keypad-style alphanumeric interface
- For redundant/mirrored applications -Two can be simply crossover-cable networked
- Compliances: UL864 (Control Units for Fire Protective Signaling Systems); UL1610 (Central Station Burglar Alarm Units).



# **iSee Video**<sup>™</sup>**:** Affordable Professional Quality Hi-Res. Remote Video - Use alone or integrate with iBridge





#### iSee Video<sup>™</sup>: Affordable Professional Quality Hi-Res. Remote Video pioneered by Napco...

Napco pioneered remote video and today's iSee Video is the reliable, easyto-install, ideal upsell solution for residential & smaller commercial accounts.

It's the affordable remote video service accounts want, where kids, pets, elders or employees, boats or vacation homes are viewable on any PC or smartphone anywhere, 24/7. They'll view live streaming video, archived or emailed events from a supplied secure multilingual website we provide, that security companies can customize with their logo, phone, URL and contact info. It can be deployed with any of three indoor or outdoor iSee Video 802.11 WiFi Camera, with a secure-networked installation in as little as 10 minutes, or you can use your choice of analog camera brand, instantly converted to IP cameras with our Video Gateway. Both methods give you and your residential or commercial customers the high-res. professional quality iSee Video online remote video service you'd expect from Napco. And, now iSee Video is a featured application integrated in the iBridge suite of connected home services, including the iBridge App for Smart Devices and on the iBridge Touchscreen/Tablet Computer. (see pages 7 - 10)



# iSeeVideo<sup>™</sup> Remote WiFi Video:

The easiest, the first, the best.



#### WiFi, Hi-Res., streaming video, viewed 24/7 on-the-fly or capturing an event, sent to client's smartphone or computer online, anywhere.

Fast installs with WiFi indoor/outdoor cameras that autoenroll and secure-lock their video network. Hi-res fullframe viewing, and fastest frame rate for live streaming video – not herky-jerky little screens that can't be blown up.

#### WiFi Camera Features

- Put video accounts online in as little as 10 minutes
- Upsell your residential & small business alarm accounts on very affordable video for incremental RMR
- Highest resolution remote video on the market! 20 frames per second at VGA res. (640x480)
- 802.11 cameras easily enroll on network with patented wireless access point's auto-detect mode (All have a hardwire jack option too.)
- Free Apps. iPhone/iPad, Android
- Professional quality -View online in quad screen configuration or by-camera, Quickly review archived video with film-strip style thumbnails with time/date-stamp
- Customize with your company logo & phone on view screen to keep your name in front of accounts
- Choice of Wi-Fi Cameras, pan & tilt, outdoor/waterproof or fixed IP, in all-inclusive turnkey kits, include one year of subscriber service. *Also, new Megapixel Camera with IR and built in PIR (shown).*

### Our Camera or Yours...

Put any analog camera of any brand online easily with iSee Video remote service using the **Single Channel Gateway**, **model ISEE-SCHGW/12**, that instantly converts any analog CCTV camera into a high-res. internet-ready IP camera online (use up to 6 per account). Streaming or stored video can then be remotely accessed anywhere in the world, 24/7, from any web-enabled computer or smartphone with Free Apps. for iPhone/iPad, Blackberry, Droid. Plus using optional alarm system input triggers, video can be automatically captured and/or emailed to accounts upon alarm events, such as business opens/closes, returning children (disarm), retiring of elder parent (arm), departure of staff (cleaning people or service contractors).

#### **Single Channel Gateway Features**

- Simply plug the CAT5 cable into premises' router and the camera will automatically adapt to the network regardless of service and modem type. Even in the most inflexible corporate networks, the video camera will auto-configure through the network to iSee Video's www.videoalert.net server.
- Professional widescreen VGA, high-res. video images of 704 x 480, max.using MPEG4 compression
- Fast 20FPS video viewing on the Napco-provided server including 12-months subscriber access to 50MB of video storage. Or, for full-time recording, use the affordable iSee Video Internet Video Recorder (IVR250, below).
- View online in quad screen configuration or by-camera, Quickly look-up archived video with film-strip style thumbnails with time/date-stamp
- -or- advanced pixel-based motion detection on demand or on event, can transmit video clips to the www.videoalert.net server and/or provide a "video alert" to the account 's smart phone/ tablet
- Local TV viewing option Gateway provides a local video output for optional signal for BNC video-in/-out connection to a monitor, or for local distribution, using a video modulator. – Great for viewing outdoor cameras while clients remain safe & comfortable inside.
- Free Dynamic IP support

#### IVR250 & IVR-250-1T

# iSee Video Internet Video Recorder for Full-Time Recording

 Continuously record and store 30 to 90 days of video from up to six iSee Video System cameras with our new Internet video recorder (ISEE-IVR250 for 30 days or -IVR 1T for Terrabyte Storage, 90 days)

# **iSeeVideo Cameras** iSeeVideo Wi-Fi IP Indoor & Outdoor Cameras

	<b></b>	9		2	
IP Camera	Wireless Fixed IP	Wireless Pan/Tilt IP	Outdoor Wireless Fixed IP	Wireless Megapixel HD	Outdoor Wireless Megapixel HD
Model	ISVWLCAM	ISVWLCAMPT	ISVWLOCAM	ISVWLHDCAM	ISVWLOHD
Starter Kit	ISVWLKIT1	ISVWLPTKIT2	ISVWLOKIT3	ISVWLHDKIT4	ISVWLOKIT6
Video Image Sensor	Ominivision 7725 CMOS, 1/6" VGA Resolution	1/4" CMOS, VGA Resolution	1/5" CMOS, VGA Resolution	CMOS, 1/4" HD Resolution	CMOS, 1/4" HD Resolution
Lens:	F2.8 Fixed Focus, Effective Range: 0.2M to infinity	F2.0 Fixed Focus, Effective Range : 50cm to infinity	F2.0 Fixed Focus, Effective Range: 0.2M to infinity	F2.0 Fixed Focus Lens, Aperture:, Diagonal View Angle: 66° (Horizontal=57.8°, Vertical=37.8°	F2.0 Fixed Focus Lens, Aperture:, Diagonal View Angle: 66° (Horizontal=57.8°, Vertical=37.8°
Compression	MPEG-4	MPEG-4	H.264, MPEG-4	H.264, MPEG-4	H.264, MPEG-4
Resolution Support	640x480	640 x 480	640x480	720P HD (1280 x 720)	720P HD (1280 x 720)
Frame Rate, in VGA	30 fps	30 fps	30 fps	30 fps	30 fps
Image Control	AWB, Brightness	AWB, AGC, Sharpness, Brightness	AWB, AGC, Contrast, Brightness	AWB, AGC, Sharpness, Brightness	AWB, AGC, Sharpness, Brightness
Video options	Motion-Detection, Time Stamp,Text Overlay	Motion-Detection, Time Stamp,Text Overlay	Motion-Detection, Time Stamp, Text Overlay	4 Programmable Pixel Based Analytic Motion Detection Zones. PIR Motion Sensor Range: 15 (4.6m) with a viewing angle of 85° when installed at a height of 8: Dual Technology Motion Detection Option, PIR and Pixel based trips required for event triggering, (Pats Pending)	4 Programmable Pixel Based Analytic Motion Detection Zones. PIR Motion Sensor Range: 15 (4.6m) with a viewing angle of 85' when installed at a height of 85' ubal Technology Motion Detection Option, PIR and Pixel based trips required for event triggering. (Pats Pending)
Pan/Tilt Range		Pan: 126°, Tilt 64° + 53° View Angle, respectively			
Audio	Built-in Microphone	Built-in Microphone	Built-in Microphone	Built-in Microphone	Built-in Microphone
E-mail notification triggered by motion detection	Yes	Yes	Yes	Yes	Yes
Simultaneous Users	5	5	5	5	5
Wireless Standard	IEEE 802.11b and 802.11g	IEEE 802.11b and 802.11g	IEEE 802.11b/g/n	IEEE 802.11b/g/n	IEEE 802.11b/g/n
Range Indoor	50m	50m	50m	50m	50m
Outdoor rating			IP65 Waterproof rating		IP65 Waterproof rating
Infrared LEDs			8 IR LEDs with photoelectric cell control; Night Vision Filter	8 IR LEDs with photoelectric cell control; Night Vision 40' range	8 IR LEDs with photoelectric cell control; Night Vision 40' range
Encryptions	WPA, WPA2, 128bit WEP	WPA, WPA2, 128bit WEP	H.264, WPA, WPA2, 128bit WEP	128 Bit WPA	128 Bit WPA
NAPCO Automatic Secure Enrollment (Pats. Pending)	Yes	Yes	Yes	Yes	Yes
Working Temperature	-5°C to + 50°C	-5°C to + 50°C	-15° to 45°C	-15° to 50°C	-15° to 45°C
Power Adapter	5V / 2A, 100 / 240 VAC	5V / 2A, 100 / 240 VAC	5V/1A, 100/240 VAC	12VDC/1A, 100/240 VAC	12VDC/1A, 100/240 VAC
Certification	CE / FCC	CE / FCC	CE / FCC	CE / FCC	CE / FCC
Dimensions (HxWxD)	3.8 x 3.5 x 1.4"	5.7" x 3.8" x 3.1"	3.8" x 3.5" x 1.4"	3.6" x 2.4" x 1.4"	3.8" x 3.5" x 1.4"

#### Ordering Information for iSeeVideo Wireless Cameras/Kits & Accessories

ISVWLKITI Complete Wireless Camera Kit: One (1) 802.11 Wireless Fixed Camera, 640x480 hi-res, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access.

ISVWLPTKIT2 Complete Wireless P/T Camera Kit: One (1) 802.11 Wireless Pan/Tilt Camera, 640x480 hi-res, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access.

ISVWLOKIT 3 Complete Wireless Outdoor Camera Kit: One (1) 802.11 Wireless Weatherproof (IP65) Fixed Camera, 640x480 hi-res, with built-in PIR motion detector, 6 IR LEDs with photo cell activation and night vison filter, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access.

ISVWLHDKIT4 Complete Wireless Megapixel Camera Kit: Kit as above but with one (1) 802.11n Wireless HD Megapixel Camera, : 720p HD (1280x720), Infrared (IR), built in PIR (3.8"H × 2.5"W × 1.4"D (plus base, approx 3"sq.); power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access. ISVWLHDKIT6 Complete Outdoor Wireless Megapixel Camera Kit: Kit similar to above, but with one (1) 802.11n Wireless HD Megapixel Dual Antenna Outdoor Camera, IP65 Rated, : 720p HD (1280x720), Infrared (IR), built in PIR (3.8"H x 3.5"W x 1.4"D (plus base, approx 3"sq.); power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access.

ISVWLCAM Add-on 802.11 Wireless Fixed Camera: 640x480 hi-res AC transformer (Kits support up to 6 cameras). Includes 12-months iSee Video Network access.

ISVWLCAMPT Add-on 802.11 Wireless Pan/Tilt Camera: 640x480 hi-res, power adapter (Kits support up to 6 cameras). Includes 12-months iSee Video Network access.

ISVWLOCAM Add-on Outdoor 802.11 Camera: Wireless Weatherproof (IP65) Fixed Camera, 640x480 hi-res, with built-in PIR motion detector, 6 IR LEDs with photo cell activation and night vison filter, power adapter. (Kits support up to 6 cameras). Includes 12-months iSee Video Network access.

ISVWLHDCAM Add-on 802.11 Wireless HD Megapixel Camera with Infrared (IR) and built in PIR: 720p HD (1280x720), IR, PIR, AC transformer. Includes 12-months iSee Video Network access. ISVWLHDOCAM Add-on Outdoor 802.11 Megapixel Wireless Camera with IR and PIR: Similar to two prior models, but HD performance, in Outdoor, IP65 Rated Version. Dual antennas. 3.8" x 3.5" x 1.4"

ISV-REPTO1 Optional Repeater will extend the range of cameras that are located away from the WAP (place approx. half way between WAP and farthest camera. One/Sys).

ISEE-IVR-250-1T Optional One-Terrabyte Internet Video Recorder Provides full time hi-res (640 x480) recording of up to 6 cameras for at least 90 days with full review and easy search functions. Fully, supervised; an ideal replacement for old DVRs, plus a new RMR stream.

ISEE-IVR-250 Optional Internet Video Recorder, as above, but recording of up to 6 cameras for 30 days.

www.napcosecurity.com/video.html



# Gemini Remote Virtual Keypad Module & App: Easy affordable remote security system control.

# iRemote



"My Remote Keypad" App for iPhone/iPad and Droid.

#### **IREMOTEMOD/12**

- Remote keypad access anywhere, works & looks like any Gemini keypad model.
- Supports all Gemini model panels and keypads
- Remote control Gemini Virtual Keypad with Free 12-months account access on Free custom dealer web site
- Simply wire iRemote<sup>™</sup> Module on the panel's keypad bus.
- Exactly mirrors keypad on premises for easy 24-7 control via web and PC or smartphone
- 100% full-function "keypad" for easy remote troubleshooting without making a service call

- Bonus functionality Up/download to panels via internet in just seconds; alarm reporting to central station via internet
- Free downloadable apps for iPhone/iPad, Blackberry, Android
- Panel Compatibility GEM-X255, GEM-P9600, GEM-P3200, GEM-P1664, GEM-P1632, GEM-P816

#### **ORDERING**:

- iRemoteMod/12 Module with 12 months subscriber access, included
- **iRemote64Pak** with GEMP1664 4-Area Panel, Talking GEMK1VPS Keypad and transformer, and iRemoteMod/12.





### Smart Keypads to Smart Homes -





### Door-style keypads

#### GEM-DK1CA

- Contemporary, pure black and white styling
- Door covers keys for cleaner lines & prevents unwarranted use
- Bright blue backlit custom LCD display & alphanumeric zone directory
- Blue backlit keys brighten to the touch and feature easy stay and away functionality
- Built in 4-zone expander
- 3 built in panic buttons
- Familiar Napco operation, identical usage and programming to GEM-K1CAe2
- Distinctive new look distinguishes dealers from competitive alarm companies

(Also available in digital model GEM-DK3DGTL, shown left)

# *Talking,* Multifunction Keypad with voice assist, UL siren & pet PIR built in

#### GEM-K1VPS

- For use with GEMP1664 and GEMP1632 Panels, for 64 or 32 user codes, each
- Talking voice prompts (adjustable volume)
- Large blue custom alpha display
- Built-in 88db burg/fire alarm siren (temporary hush mode)
- Built-in wide-angle 25' pet PIR and smart occupancy sensor
- Supports event log viewing
- Optional temperature display (with GEM-TEMP64 module) (see Gemini Accessories pg. 23)



## Gemini Makes it All Simple.

#### GEMINI



#### Custom alphanumeric keypads

#### GEMK1CA and GEMRP1CAe2

- Deluxe 32-character backlit, menu-driven, dual-line display
- Custom alphanumeric zone directory
- Built-in 4 Zone expansion module
- Display of wireless transmitter signal strength 1-10
- EZ Keypad Programming2 with actual Q&A's
- Intuitive, stay & away ease-of-use buttons, for easy one button arm and easy instant (hold-down) with the GEMK1CA. Traditional interior and instant keys with the GEMRP1CAe2
- Large soft touch backlit keys with tone
- Backlit displays for easy reading
- Wireless transmitter signal strength indication
- Fire, police and auxiliary programmable panic keys
- Fingertip reference chart



#### Alpha/symbol keypads

#### GEMK2AS and GEMRP2ASe2

- Unique backlit, combination alphanumeric and symbol display
- Intuitive, stay & away ease-of-use buttons, for easy one button arm and easy instant key (hold-down) with the GEMK2AS. Traditional interior and instant keys with GEMRP2ASe2
- Large soft touch backlit keys with tone
- Backlit displays for easy reading
- Wireless transmitter signal strength indication
- Decor friendly soft white design
- Fire, police and auxiliary programmable panic keys
- Fingertip reference chart



#### Keypad with built in wireless 32 pt. Gemini RF receiver

#### GEMK4RF

- Built-in 32 Point Gemini wireless receiver for labor-saving convenience
- Large backlit, fixed English display
- Proven crystal-control wireless performance
- Supports all Gemini transmitters
- Intuitive, stay & away ease-of-use buttons, for easy one button arm and easy "instant" (hold-down)
- Large soft touch backlit keys with tone
- Wireless transmitter signal strength indication
- Decor friendly soft white design
- Fire, police and auxiliary programmable panic keys
- Matching keypad without-receiver GEMK4



### Digital keypads

#### GEMK3DGTL and GEMRP3DGTL

- Vivid dual 7-segment digital display keypad
- Intuitive, stay & away ease-of-use buttons, for easy one button arm and easy instant (hold-down) with the GEMK3DGTL Traditional interior and instant keys with the GEMRP3DGTL
- Large soft touch backlit keys with tone
- Backlit displays for easy reading
- Wireless transmitter signal strength indication
- Decor friendly soft white design
- Fire, police and auxiliary programmable panic keys

## Smart Keypads to Smart Homes - Gemini Makes it Simple.





# 

#### 800-Series' classic custom alphanumeric keypad with stay & away keys

#### GEMRP8LCD

- Deluxe 32-character backlit dual-line custom alpha display & directory
- Built-in 2 zone expansion module
- Display of wireless transmitter signal strength



#### GEM-K800 and GEM-RP8 numeric LED keypads

- Backlit keys and vivid red LED numeric display
- Traditional-key style GEM-RP8 supplied with GEMP801/P800
- Stay & Away version GEM-K800 available

Touchscreen/Tablet, Wireless WiFi or Hardwire Models IBR-ITAB / IBR-TAB-HW

#### For Use with Gemini Panels

- Touchscreen control of security system and more from anywhere in the home
  - Thin, slim profile
  - Color full-screen TFT high-resolution display (800 x 480)
- Provides full Gemini Keypad Security functions, in GUI or conventional keypad mode.
- Optionally integrates with iBridge Smart Automation &/or iSee Video Camera viewing
- Web browser-enabled
- Handy on-screen tools: Message Minder (recordable voice messages with playback); weather, calculator, etc.
- High-speed, powerful processor
- Easy on/off magnetic wall mounting frame & charger dock



#### Express LED/Door Keypads

(for Express panels only)

#### RP-X6 & RP-X4

- Door-styling, conceals keys Backlit keys and
- Multilingual , vivid LED symbol & numeric display
- RPX-6 supplied with XP600; RPX-4, with XP400

#### Gemini BioReader Outdoor Digital / Fingerprint Keypad



#### GEM-BIOREADER/MS

 Indoor/outdoor digital keypad with a highly-advanced and accurate optical biometric fingerprint reader for integrated control of any Gemini security system or as state-of-the-art standalone access control use for alarm systems, garage door operator control, lighting, etc. with relay activation.



- Increases the security of the system Biometric ambush feature sends silent alarms. Use pre-selected and enrolled finger to silently call the police during push ins and robberies
- Convenient for consumers- No keys or cards to carry, no codes to memorize and remember
- Eliminates code pass-along. With children or employee-turnover - you can't pass along a fingerprint!
- Users. System supports 100 biometric fingerprints, that can be mapped to Panel User Codes for logging who armed/disarmed.
- Supervised (e.g., reports if unit is ripped from building)
- Duable metallic silver powder-coat finish.

*Residential applications* Keyless use ideal for children; Memory-free for elderly; Easy Residential alarm and garage door control.

*Commercial applications* such as gate control and parking lot access; restricted access to sensitive pharmaceuticals, weapons, supplies and more.



### Bi-directional LCD keyfob compatible with all major alarm panel brands **2WAY-UNIVKFKIT**

- Bidirectional keyfob with LCD status icon display and sounder.
- System Status is indicated on its LCD display with 8 intuitive icons (a lock, a house, a flame, etc.) plus corresponding audible beeps
- Universal panel compatibility with most major control panel brands, using bus or keyswitch input (including bus operation on NAPCO's Gemini & Magnum plus Honewell)
- Complete kit with dedicated 2-way Keyfob Receiver and one fob in 2WAY-UNIVKFKIT; or add on up to 6 more fobs, sold separately 2WAY-UNIVKF



Universal value keyfob... works with any alarm panel brand with keyswitch

#### **UNIVKIT1**

- Simple 2-button Arm/Disarm operation with LED indicator; optional panic
- Works with all control panel brands with keyswitch input
- Long range yet compact
- Complete kit with dedicated Keyfob Receiver (1-way) and one fob in UNIVKIT; or add a second keyfob (max. 2), sold separately UNIVKF1

# **Napco.** The 1st Security Partner Integrating Control4 SDDP and Control4 via Ethernet





Integrate a Napco Gemini Security System as part of a Control4 system for seamless, smarter integration & easiest, fastest setup & installation.

- Napco Gemini Expandable Hybrid Panels are integrated and Control4 Certified
- By exclusively integrating with Control4 SDDP, the Control4 Controller can automatically recognize the Napco Gemini Security Panel, enabling you to quickly and accurately install it in a Control4 project, saving time and personalization data.

- ALL Gemini Expandable Panels, GEMP816 to X255
- Smarter Automation Use Any or All Detected Napco Gemini Zone Activity as Integrated Event Triggers for the C4 System
- Supported with All Gemini Keypads Classic & Stay/Away Models
- Convenient Napco/Control4 Turnkey Kits available from Control4 Online Store & Training at Control4 University
- Today's Truly Seamless Smart Home & Sophisticated Security Integration



Even Better Together Gemini Security Systems: Flexible and more options than ever - including remote services,



### **Expandable Gemini** hybrid controls feature:

- Wide choice of designer keypads for every application and budget
- iBridge App & Touchscreen/Tablet for integrated security, climate, lighting or video control or iRemote Virtual Keypad App for smartphones/devices
- Control4<sup>®</sup> Certified SDDP and Ethernet Integration C4 Controller can seamlessly use all Napco Bus detected activity for triggering home automation.
- Support all major communication formats plus internet & StarLink Wireless Radios, universal primary/backup communicator (hi-speed up/ downloads from Gemini Panels)
- Up/downloading, including unique PC-preset unattended method
- EZ-Programming mode at keypad
- Choice of Gemini RF receivers & transmitters
- Multi-stage lightning protection
- Event log with open/closes suppression
- Telco line cut supervision
- Fuseless, maintenance-free operation
- Transformer, supplied

Gemini X255 is the expansive hardwire/wireless control offering 255 fully-programmable zones, 195 users, fuseless operation & supports the full line of top performing Gemini Wireless

#### Features:

- 8 to 255 hardwired zones or wireless zones/ pts
- Expandable using 8-zone GEM-EZM8 expansion modules
- Up to 96 fire zones, with 8 2-wire fire zones
- Up to 8 areas
- Up to 195 user codes with open/close by user
- 3 On-board relay output & 1 prog. lug
- Up to 96 relays
- Supports 4 wireless receivers
- Supports 15 GEMRP1CAE2 or K1CA keypads
- Up to 2 interior bypass groups
- 800 Event log w/ open/close suppress
- Auto arm/disarm
- 255 Event scheduler
- GEM-ACCESS access control compatibility

#### Gemini P9600 powerful multi-tasking hybrid control panel - feature-rich for security applications and home automation integration

#### GEMP9600 (cont'd)

#### Features:

- 8 to 96 hardwire zones/points
- Including 8 2-wire fire zones
- Up to 96 user codes
- Up to 8 areas
- 3 On-board relay outputs; expandable to 96
- 1 On-board programmable lug
- Up to 4 RF receivers
- Up to 15 keypads
- Up to 2 interior bypass groups
- 800 Event log
- Auto arm/disarm
- 255 Event scheduler
- GEM-ACCESS access control compatibility

#### Gemini P3200, a popular, allaround 8 zone hybrid control expandable to 32 zones or 48 wireless points

#### Features:

- 8 to 32 hardwire or wireless zones/points; up to 48 RF wireless points
- Including 2 2-wire fire zones
- Up to 48 user codes
- Up to 2 areas
- Fuseless, maintenance-free operation
- 3 On-board relay outputs; expandable to 24
- 1 On-board programmable lug

### Apps, optional WiFi touchscreen & cellular communications

#### GEMINI

- Up to 2 RF receivers GEMP3200 (cont'd)
- Up to 7 keypads
- Interior bypass groups
- 800 Event log
- Auto arm/disarm
- 255 Event scheduler
- GEM-ACCESS access control compatibility

#### **Gemini P1664**, 4-area hybrid panel with 8-64-zones of power; supports all keypads plus talking multifunction keypads with built in siren & pet PIR

- 8 to 64 hardwire or wireless zones
- Up to 64 fire zones, with 2, 2-wire fire
- Up to 64 user codes
- Up to 4 areas
- 400 event log; viewable at custom alpha keypads
- Up to 2 RF receivers
- EZ Programming at keypad and Auto Arm
- Supports up to 7 keypads: all standard Gemini Keypads and/or talking, multifunction GEM-K1VPS (may be intermixed)
- Supports 3 outputs; expandable up to 16 external outputs (RB/RM3008)
- 2 PGM outputs
- 1 interior zone group; 2 prog. chimes by zone;
- SIA CP01 features

### Gemini P1632, ultra-popular

#### hardwire/wireless control panel with partitioning – easy to standardize for both residential & light commercial applications

#### Features:

- 8 to 32 hardwire zones/points
- Including 2 2-wire fire zones (7;8)
- EZ programming at keypad
- Up to 32 user codes
- Up to 2 areas
- Supports up to 7 keypads and/or talking, multifunction GEM-K1VPS (may be intermixed)
- 3 On-board relay outputs; expandable to 8 relay outputs
- Up to 2 RF receivers
- Interior bypass groups
- 400 Event log
- Auto arm

#### **Gemini P816**, an economical hardwire/wireless control panel that works seamlessly with all standard Gemini keypads and wireless

#### Features:

- 8 to 16 hardwire zones/points
- Including 2 2-wire fire zones

- Up to 16 user codes
- GEMP816 (cont'd)
- Supports up to 7 keypads
- EZ Programming at keypad
- 256 event logging
- Supports 2 Gemini receivers
- Interior bypass group
- Auto arm
- 3 Outputs

#### **Gemini P801**, economical 9 zone hybrid with your choice of numeric or custom alpha keypads

#### Features:

- 9 Programmable zones: 6 Hardwire or wireless zones plus 2 wireless zones plus 2-wire fire zone
- Use 2 optional zones at GEMRP8LCD custom alpha keypad
- For Control packed with RP8LCD Custom Alpha Keypad, order GEM-P801ALPHA
- For control packed with RP8 Numeric LED Keypad, order GEM-P801
- Uses GEMRECVXP8 wireless receiver
- 8 Individually reporting user codes
- 50 Event log
- Line and bell-cut supervision
- Double reporting & backup reporting
- EZ wire full-size terminal strips

#### **Gemini P800**, ultra-affordable hybrid control includes numeric keypad and 6 zones plus fire and panic

#### Features:

- 8 programmable zones, including 2-wire fire zones
- Up to 16 Gemini wireless points: 8 wireless points from your choice of Gemini PIR, window/door & glassbreaks
- Up to 4 Gemini wireless smoke detectors and 4 GEMKEYF fobs
- 8 individually reporting user codes
- Supports up to 4 GEM-RP8 keypads &/or 2 wireless receivers (GEM-RECVXP8)
- Supports GEM-R8LCD/K800 Custom Alpha Keypad
- Includes control, Numeric LED Keypad and transformer

#### **Gemini Accessories**

#### GEM-EZM4/8 Expansion Module

Economy 4 to 8 zone expansion module supports GEM-P816, GEM-P1632 & GEM-P1664

#### GEM-EZM8 Expansion Module

 Eight-zone expansion module (for all expandable GEM panels. Audible find mode)

#### GEM-PRINT

Module that enables Gemini system activity to print

to an on-site parallel printer

- For use with GEMP816 to X255 Controls
- **IBRIDGE & IBR-ZREMOTE MODULE**

**iBridge App for iPhone/iPad & Droid** smart devices or optional **iBridge Touchscreen/Tablet IBR-ITAB** wireless WiFi 802.11 portable full-color tablet with on/off magnetic wall-mount/charger dock. Control alarm & video plus lights, temp., locks with bus-mount Z-Wave Module plus Z-Wave Devices. For GEM Panels, X255 thru P816 (Includes 12 Mos. Subscriber Service.) (see page 22 & 23).

#### IREMOTEMOD/12

Gemini Virtual Keypad module provides a mirrorimage, fully-functional, remote control keypad on a on any PC or smartphone online anywhere in the world (free apps for all smart devices.) Module simulates real keypad model at physical premises and simply wires on GEM-Panel's keypad bus. (see page 17)

#### GEM-TEMP64

Indoor/Outdoor Temperature Sensor provides Temperature Display at any Gemini Alphanumeric Keypad in a GEMP1632 and GEMP1664 System. Keypad will show Temperature in display, from -30 to 60C or -22 to 140F (replacing "Date" on keypad-display), e.g., GEMK1VPS, GEM-DK1CA, GEM-K1CA, GEM-RP1CAe2. Module is mounted inside or outdoors, to display either the temperature outside or inside room temperature. Tip: If used with IREMOTEMOD Module (below), the virtual keypad shown on the consumer's iPhone or laptop includes that temperature. Example, in a remote vacation home or hunting cabin, the unit can be mounted inside so endusers can check in remotely from anywhere, and make sure the room temp. is sufficient, preventing frozen/burst pipes etc., likewise knowing if and when an HVAC system fails, can help prevent damage/molds in heat.

# **Express Systems** with multilingual LED XP keypads

#### XP400WK, XP600WK, respectively

- Feature-rich programmable zones:
- 4 in XP400 -or- 6 in XP600
- Support all Gemini wireless transmitters
- using Gemini GEM-RECVXP8
- Includes multilingual LED keypad (suffix -SN for Spanish language zone dir'y); RP-X4 for XP400 or backlit RP-X6 for XP600
- Keyfob support: 2 or 4, respectively
- Plus 4 or 8 pts, respectively, for RF points from choice of PIR, window/door & glassbreaks
- Plus XP600's 2-wire fire zone also supports 4 wireless Gemini smoke detectors
- 4 or 6 Individual user codes, respectively
- Available in 4-Paks with 4 keypads, part no. XP400/4 or XP600/4

# Gemini Wireless: Proven to outperform the competition

GEMIN

WIRELESS

Napco's crystal-control Gemini wireless products have been proven by an independent testing laboratory to outperform competitive products, with longrange RF reliability, as much as 50% higher than other top brands.

Gemini Transmitters range from keyfobs and panic buttons, to recessed door and surfacemount window/door contacts, to wireless PIR, PIR/pet and dual sensors, and from wireless smokes and glass breaks to heat detectors. Simply put, Gemini's uncommon crystal-control precision and omnidirectional circuitry, ensures the wireless/hardwire systems you provide your customers will dependably deliver the security and troublefree, peace-of-mind they deserve for many years to come.

#### Advanced performance Gemini RF receivers

GEM-RECV-XP8 8 Points For Express, P801/800/P400 panels, only GEM-RECV-32 32 Points GEM-RECV-96 96 Points

#### GEM-RECV-X255 255 Points

- Dual diversity antennas minimize nulls & enhance reliability
- Tamper- and RF-jamming supervision
- Separate programmable supervisory times by device type
- Audible fault-find mode in walk test
- Also, fixed English language keypad GEM-K4RF with built in 32 pt receiver (see keypads section).

See Great Wireless Paks, pgs 36 & 37

# Low profile wireless window/door transmitter

#### GEM-TRANSLP

- Ultra compact design, 2.5 x 1 x 0.4 (H x W x D inches)
- Tamper supervised
- Replaceable lithium PL2O32 coin cell battery (supplied
- 5-year battery life, typical
- Magnet and Internal reed switch
- External lead (24" mini connector pigtail) for wiring external devices (jumper-selectable)
- Magnet mounts with either supplied double-face tape or screws (screwtabs easily removable from mounting plate, at score)

#### **GEM-RTRANS** (not shown)

For recessed use in windows & doors





Now in Brown, too, GEM-TRANSLP-BRN



GEM-TRANSLP virtually disappears even in slimline window frames

#### Wireless Carbon Monoxide Detector

#### GEMC-WL-CO

- For use with Gemini & GEMC Comm'l Grade Receivers GEM-/GEMC-RECV
- 5-3/8 diameter and approx. 2" profile, uses a 3V Lithium Battery (CR123A) for long life
- Monitor alarms, restores, low battery, tamper and status
- UL 2075, UL 2034

# Wireless window/door transmitters

GEM-TRANS2 2-Points

- Soft white, compact, low profile
- Reversible mounting position for left or right handed operation
- Low battery clearly displayed at keypad by zone and transmitter number
- Both models include built-in reed switch, magnet, lithium battery, tamper and terminals

#### GEM-TRANS2BRN25

• Field-changeable brown housings for woodgrain installation (case of 25).

# Wireless acoustic glass break detector

#### GEM-GB

- Superior-immunity to false alarms and excellent detection, even through blinds & light drapes.
- Pattern recognition technology recognizes the actual pattern of glass breaking across the full audio band.
- 25' coverage radius with automatic test for easy installation
- Enduser hand clap sensor verification
- Includes lithium battery, tamper & mounting kit

# Wireless Adaptive® dual microwave/PIR

#### GEM-DT

- Broad 40' x 40' range
- Exclusive Adaptive dual technology for superior false alarm resilienceeven from animal/pet activity and optimized catch.
- Active self-test of both sensors
- 5 interchangeable lens patterns
   One button walk-test with auto shut-off
- 3 distinct transmissions for tamper alarm and self-test failure
- EMI/RFI protected with fullyshielded SMD circuitry
- Includes batteries, tamper and mounting screws

#### Wireless PIR & Pet PIR

#### GEM-PIR

- Broad 50' x 50' coverage
- 11 interchangeable lenses
- Signal selective processing
- Auto temperature compensation
- EMI/RFI protected with fullyshielded SMD circuitry.
   Battery-saver feature
- Includes lithium batteries and mounting screws

#### **GEM-PIRPET**

 As above with 40 lb. pet/animal immunity



### Wireless photoelectric smoke detector

#### GEM-SMK

#### Designer styling and longer battery life

- Long 5-year battery life, typ. (batteries included)
- Compact 5.2 inch diameter; attractive decorator white
- Built-in silence feature and test button
- Visual LED indicates alarm & standby
- Audible/visual indicator for low battery and need for detector cleaning
   Proven Gemini ™
- wireless crystalcontrolled transmitter



# Wireless heat detector

#### GEM-HEAT

- High-quality 135°F (57° C) fixed temperature detector with rate of rise
- Reliable, crystal-controlled wireless technology
- Long-life, replaceable lithium batteries

#### Wireless keyfob/ emergency pendant transmitter

#### GEM-KEYF compact style

- 4-Button operation: 2 for On/ Off of security system and 2 programmable for Aux. functions, e.g. panic, medical, relays or relay groups, instant or X-10 control
- Visual indicator fortransmission or low battery
- Includes keyring, chain, replaceable battery, alternate icon key set for automation (lights)

#### Wireless waterproof panic

#### GEM-WP PANIC

- Waterproof personal panic button
- Worry-free peace of mind1-button operation with tactile
- feedback click
  Extra-large, soft touch button for trouble-free use even by dexterity-impaired or arthritic hands









1

# How to Build a Winning Gemini System.



# Pick a wireless device



GEM-WPPANIC WATERPROOF PANIC



GEM-DT DUAL TECHNOLOGY



GEM-KEYF KEYFOB



GEM-RTRANS RECESSED WINDOW/ DOOR

GEM-TRANSLP LOW PROFILE WINDOW/DOOR -LESS THAN 1/2" D



GEM-GB ACOUSTIC GLASS BREAK



GEM-TRANS2 WINDOW/DOOR



GEMC-WL-CO CARBON MONOXIDE DETECTOR & RECEIVERS



GEM-PIR/ GEM-PIRPET PASSIVE



GEM-HEAT

DETECTOR

#### GEMINI

		GEMINI PANELS						
	GEM	P816	P1632	P1664	P3200	P9600	X255	P801
	K1CA/DK1CA	•	•	•	•	•	•	
YPADS STAY & AWAY	K1VPS		•	•				
	K2AS	•	•	•	•	•		
GEMINI KEYPADS	K3DGTL/DK3DGTL	•	•	•	•	•		
S EYP	K4RF	•	•	•	•	•		
	К4	•	•	•	•	•		
GEM CLASSIC	RP1CAe2	•	•	•	•	•	•	
	RP2ASe2	•	•	•	•	•		
	RP3DGTL	•	-	•	•	•		
5	RP8LCD							•
	RP8/K800							•

### Pick a smart phone/tablet interface

(optional)

BRIDGE HOME CONTROLS APP FOR ANY SMART PHONE OR DEVICE\*\*





IREMOTEMOD/12 IREMOTE VIRTUAL KEYPAD MODULE (\*\*REQUIRES IPHONE/BLACKBERRY/DROID SMARTPHONE OR COMPUTER).

COR DEVICE\*\*
OPTIONAL IBR-ITAB IBRIDGE TOUCHSCREEN TABLET
(NOTE: iBridge Touchscreen may also be the primary keypad, See pg. 8).

# Pick a panel accessory



**IBRIDGE IBR-ZREMOTE** 

SINGLE Z-WAVE DEVICE & REMOTE SERVICES CONTROL MODULE

[Note: IREMOTE-MOD Also available for remote control w/o Z-Wave) GEM-EZM4/8 For P816, P1632 & P1664 ECONOMY 4 TO 8 ZONE EXPANSION MODULE

GEM-EZM8 FOR ALL GEMINI EXPANDABLE PANELS • 8 ZONE EXPANSION MODULE

> RB3008 8 RELAY EXPANSION MODULE



GEM-ACCESS ADD-ON ACCESS CONTROL (HID® OR GEM-PX)

# Pick a wireless receiver

(Choose by # of wireless points)



32 PTS: GEM-RECV32 96 PTS: GEM-RECV96 255 PTS: GEM-RECV255

# Choose communication options



# Smarter Cellular Solutions. Any Panel. Anywhere in US.







#### **SLE-GSM-FIRE**

- Universal CDMA Network full event reporting from any panel brand, virtually anywhere
- For use with all 12V-24V FACP/panels that communicate using Contact ID/4/2
- Easiest 4-Wire Installation & Activation with Dialer Capture
- Reports to any Central. NO special equipment. NO radio activation fee.
- Bonus: Full High-Speed Napco Panel remote up/downloading
  - Merchantile Versions available, in metal housing with provision for backup batteries; direct connect 120VAC or with power supply.
  - Compliances: NFPA72 Editions: 2013, 2010, 2007; UL 864, 9th Ed., UL1610, UL985, UL1023, UL1635

12V-24V FACE StarLink

#### **SLE-CDMA-FIRE**

- Universal CDMA Network full event reporting from any panel brand, virtually anywhere
- For use with all 12V-24V FACP/panels that communicate using Contact ID/4/2
- Easiest 4-Wire Installation & Activation with Dialer Capture
- Reports to any Central. NO special equipment. NO radio activation fee
- Bonus: Full High-Speed Napco Panel remote up/downloading
- Merchantile Versions available, in metal housing with provision for backup batteries; direct connect 120VAC or with power supply.
- Compliances: NFPA72 Editions: 2013, 2010, 2007; UL 864, 9th Ed.

# Firewolf Conventional Fire/ Lifesafety Devices



#### Advanced photoelectric smoke detectors

Proven to more accurately detect a wide range of fire types and to reliably, outperform conventional photoelectric detectors. Detects virtually all types of fires including paper, wood, gasoline, polystyrene, and smoldering fires.

#### FW-2 2-Wire

- FW-4 4-Wire
- Low Profile
- RF/Transient Protection
- Two built-in power/sensitivitesupervision/alarm LEDs
- Non-directional smoke chamber
- Vandal resistant security locking feature
- Removable smoke labyrinth for cleaning or replacement

#### FW2H Also available with Heat Sensor

With built-in thermal heat sensor for more fire codes requiring 135°F fixed



#### More sound in fire...

Firewolf 2-Wire Smoke Detectors with built-in 85db sounder and Line Reversal Module

FW2S Smoke Detector with built-in sounder FW-RM1 Reversal Module



# Firewolf 12/24VDC carbon monoxide detectors

#### FW-CO12 12VDC

FW-CO1224 12/24VDC (selectable)

- Designed for professional residential & commercial alarm systems
- UL2075 Listed. Tested to meet UL2034 CO response requirement
- 12 to 24VDC for varied applications
- Attractive compact styling (under 5") and neutral color for every décor
- Precise solid state infrared sensor technology & smart microprocessor optimize life safety & detection accuracy
- Patented technology: Simulates CO gas level response in human blood stream
- Independent lab tests prove superior false alarm immunity over electrochemical units (Lawrence Berkeley National Laboratory #40566)
- Powerful 85db alarm sounder & LED
- Easy Test/ Silence-Reset button

Also See New Wireless Carbon Monoxide Detector, GEMC-WL-CO, for residential and commercial systems, page 33.



#### Conventional pull stations

**FWC-CNV-PULL** Conventional Single Action Pull Station, with Hex Reset

FWC-CNV-PULLK Conventional Single Action Pull Station, with Key Reset

**FWC-CNV-PULL2** Conventional Dual Action Pull Station, with Hex Reset

FWC-CNV-PULL2K Conventional Dual Action Pull Station, with Key Reset

Note: Photo may differ slightly from actual item.

FW2-H 2-Wire with heat, FW4-H 4-Wire with heat

in thermal heat detector

Built-in thermal heat sensor for more fire codes requiring 135°F fixed.

Advanced photoelectric smoke with built-

## Napco Wired Motion Sensors: Decades of innovation inside





#### Patented Adaptive® slimline sensor and longrange version

#### C100STE & long-range model C100STLRE

- C-100STLRE 30' x 35' range
- C-100STLRE 50' x 40' range Proven, patented adaptive technology
- continuously monitors the environment, counteracting false alarms and resensitizing to optimize intruder catch
- Active self-test supervision of both microwave & PIR channels
- Wide array of interchangeable lenses
- Secured cover; tamper-supervised

Napco patented Adaptive® Microwave/PIR Sensors virtually make all other motion sensors, dual technology or otherwise, obsolete. Once they're installed, they're like having a technician on-site, making all adjustments for you 24-hours a day.

These exclusive sensors are the only ones on the market that actively & continuously monitor their environment 24/7, counteracting false alarms and re-sensitizing themselves to continually optimize catch performance. In fact, some models will even notify you if they have been purposely or accidently blocked or masked.

Ideal in all installations, despite harsh environmental conditions and/or pet/rodent activity, they provide the best protection available from both intruders and false alarms.

They pay for themselves with the first service call they prevent.

#### Commercial Adaptive sensors with mask/block supervision

#### **M7100STE**

- 40' x 40' range Active self-test supervision of both microwave & PIR
- channels
- Alarm memory with exit/
- entry delay Wrap-around shielded circuitry
- Wide array of interchangeable lenses
- 3' Dome of Protection<sup>™</sup> for anti-masking & anti-
- blocking supervision
- Secured cover
- Tamper-supervised

#### M7300STE

- M7100STE features plus:
- 70' x 60' range
- Tamper switch

#### Adaptive heavy-duty industrialstrength sensor

#### **M9000STE**

- M7300STE features plus:
- Trio-range from 55' to 120'
- EZ aim, positive locking swivel bracket
- Concealed wiring channel Vandal-resistant industrial/ institutional strength housing



- 3' Dome of Protection anti-masking/anti-blocking supervision

#### Microwave/PIR Detectors continuously adjust to their environment, providing 100lb. pet/animal immunity and ultimate reliability & false alarm protection

#### C200AP with P.E.T.™

The best pet immunity for any size animal

- P.E.T. ™, Profile enhanced targeting circuitry provides up to 100lb. (45.36Kg) pet immunity
- 40' x 40' maximum broad range
- Compromise-free intrudercatch and false alarm protection - ideal when the pet leaves the room, too.

Dynamic adaptive technology literally adjusts to its surroundings minute-by-minute, once the pet vacates the detector again elevates its sensitivity, mode by mode

- Smarter Systems<sup>™</sup> panel & sensor integration input
- Superior RFI/EMI lightning protection with wraparound shielded SMD circuitry
- Twin-Tee fluorescent light interference filter Self-test
- 2 Field-changeable lenses supplied
- Range control & auto-temp compensation



### Feature-packed advanced passive infrared sensors

#### Microprocessor PIR with 65lb pet immunity & built-in room-temp alert

#### PIR1680PT

- 45' x 45' range
- 65lb pet/animal immunity
- Room-temp alert temperature monitoring provides auto-alert at 40°F - 90° F
- Look-down/creep zone
- D.C.I.D. Technology- detect & compare imaging diagnostics for advanced false and true alarm detection
- Active self test mode
- Exceptional RFI-/EMI/lightning shielding of key components
- Lens bank available, including long range, barrier, and specialty ranges
- Wall or corner mountable
- Tamper supervised
- Form A relay

#### PIR1680

 Standard model as above, but with 20lb. pet/animal immunity



#### Advanced 70' PIR

#### PIR1710

- 70' x 60' Broad range coverage perfect for both residential and commercial
- Features look-down/creep zone
- SSP<sup>™</sup> (Signal Selective Processing) for the easiest and most stable of installations
- Auto temp compensation
- Advanced, EZ-Aim fresnel lenses and lens bank for optimum detection performance
   Wall or corner mountable
- Excellent EMI-/RMI-/lightning protection with resilient SMD circuitry
- Tamper supervised
- Form A relay

#### IQ PROFILER™

- 50lb. pet immunity (22.7Kg) & superior false alarm discrimination with unique dual focal lenses.
- Installation in a snap with patented Quick-Mount and Quick-Wire terminals
- Maximum range: 50' x 50'
- New & improved quick-catch mode
- Décor white bi-optic contour case and dual focal lenses provide exceptional distance profiling
- Far field lens allows for detection of large objects and ignores small targets nearby
- Near field lens allows for discrimination of small targets nearby
- Shielded high-performance aspheric lenses plus look-down/creep zone
- Sensor chamber prevents insect, draft, and dust interference.
- 20V/m RF-shielded circuitry



Step 3. Insert wires in Duick Wire terminals and flip down.



ra. Ire file



# Economical PIR sensor with look-down

#### PIR1510

- 30' x 30' broad range coverage
- Attractive, super-compact size
- SSP<sup>™</sup> (Signal Selective Processing) for the easiest and most stable installations
- Advanced, EZ-Aim fresnel lenses and lens bank for optimum detection performance
- Long-range, barrier and specialty lenses are available to suit all coverage needs
- Wall or corner mountable, with horizontal and vertical adjust
- EMI-/RMI-/lightning protection with resilient SMD circuitry
- Form A relay
- PIR1500 version also available, as above, without look-down/creep zone.

#### IQ VISION Advanced PIR with "IQ Look" and now all-

with "IQ Look" and now allwhite styling

- 40' x 40' range; 30lb. pet immunity
- Features look-down/creep zone
- SSP<sup>™</sup> (Signal Selective Processing) for the easiest and most stable of installations
- Auto temp compensation
- Advanced, EZ-Aim fresnel lenses and lens bank for optimum detection performance
- Excellent EMI-/RMI-/lightning protection with resilient SMD circuitry
- Tamper supervised
- Form A relay (Form C option)
- Long-range, barrier and specialty lenses are available to suit all coverage needs
- Wall or corner mountable, with horizontal and vertical adjust



#### The pet-immune PIR with Quick-Catch that profiles false alarm sources and virtually installs itself

For decades, NAPCO's innovative technology has produced sensors with superior false alarm discrimination. Today NAPCO is a leader in smart PIR technology, P.E.T. immunity, and décor-enhancing design.

# **Gemini Access:** Add Access Control to Gemini Alarms from the P3200 to Napco Commercial GEMC-Series



Integrate Access with Intrusion Systems:

• Cost efficient access solution, easily added & installed, affordable for even small to mid-size installs

 Seamless Integration with Gemini Control Panels GEMP3200, P9600, X255, GEMC; Napco Commercial Systems easily programmed with Napco Quickloader (single site programming and shared database)

 Supports HID & Gemini Prox Cards and Readers (both offered in money-saving

#### kits)

- Optional PCD-Manager enduser software for corporate security or personnel departments, etc. Easy-to-use enduser Windows-based package for account management and self-maintenance provides limited enduser account control: Manage database of both alarm users and up to 1000 access control cardholders, logs, schedules, access groups, etc.(see right).
- Plug and play GEM-ACCESS comes ready with its own enclosure, power supply (aux. for prox readers and mag locks) and battery backup. (GEM-ACMID)
- Fast card processing transaction speeds
- Easily expandable by-door with affordable GEM-2D Plug-in PCBs
- Supports HID or Gemini Prox (GEM-PX) Cards & Readers

#### **Gemini Access**

#### Ordering Information:

**GEM-ACM1D** Access Control Module for 1 door module in metal enclosure, w/ power supply, transformer and software enhancement upgrade EPROM for Gemini alarm panel.

GEM-2D 2nd Door plug-in PCB, for use in above.

# **GEM-1DKIT** Economical GEM-PROX Kit Module in enclosure, w/ power supply, transformer, panel prom, GEM-PX prox reader with status LED indicators, 25 Gemini prox cards.

 $\ensuremath{\mathsf{GEM-1DKITA}}$  HID reader kit, as above, with HID Reader and 25 HID 1326 prox cards

GEM-PX Gemini prox reader with access and alarm status indicators GEM-PXC/50 50 Additional Gemini prox cards

GEM-H1326 HID prox peader

GEM-H1326C/100 100 Additional HID cards

**PCD-MANAGER** *INCLUDED* with GEM-Access (see below) on-site mgt. software

### Gem-Access' **PCD-Manager** enduser software for client security/ personnel departments

# Increases ID cardholder capacity to 1000

Napco's GEM-ACCESS Alarm/Access Control Integration System, supported by the GEMP3200, P9600 & X255 and Napco Commercial GEMC Security Panels, enables



you to give your accounts optional Windows-based software to give their security and/or personnel departments limited control of their premises' alarm and access systems and authorized users, while safeguarding your system configurations, dealer codes, account ID's, central station number, etc. safely away from view. Plus, dealers can personalize the look of the account's software to represent their company, including options for uploading alarm company logos, website, tech support contact info., etc. with easy-to-use dealer customization utility built in.



GEM-ACMID adds integrated access control to the burglar alarm functions of the GEMP3200, 9600, X255 and GEMC Napco Commercial Systems

#### Easy account self-management interface for routine tasks, like adding alarm users/ID cards

- Easy personnel management for both alarm users (keypad user codes) & ID access cardholders
- Adding/editing/deleting personnel
- Importing text file names/data (including those from personnel files)
- Now supports the Windows Quickloader "Extended Export Files", so you can import cards and personnel directly from the Windows Quickloader.
- Viewing event logs
- Create and manage up to 195\* access groups via intuitive drop-down menus and helpful screens (\*see capacities chart, right)
- Assign users and/or access groups to easy-to-set schedules with pop-up calendar selections, drop-down menus, etc.
- Helpful Finalize Changes Summary screens summarize changes in a data-entry session for review before changes are made and downloaded.

- Comprehensive error-checking utility helps avoid errors and flags conflicts
- Report Print Manager Alarm system users/info., cardholders, scheduled events & holidays & logs.
- Easy PCD-Manager link to panel via all standard Napco download modes (locally via serial COM port; remotely via telco line or remotely via TCP/IP network)

#### Gemini Access capacities, maximum by panel

Panel	Doors	Access Groups	Total Cards &/ or Alarm Users	Expanded Cardholders (w/ PCD-Manager)
GemC	8	195	195	1000
X255	8	195	195	1000
P9600	8	96	96	1000
P3200	4	48	48	1000



# NEW!

## Gemini Wireless: Proven to outperform the competition



#### **GEMC-WL-CO**

### WIreless Carbon Monoxide Detector (for for Gemini, FIrewolf & GEMC Commercial Systems & Receivers)

- High-Quality carbon monoxide detector
- Supervised, digitally coded wireless transmitter
- Visual and audible alarm and low battery indicators.
- For use with Gemini and Gemini Commercial Grade Wireless Receivers GEM-RECV and Commercial GEMC-RECV Series
- 5-3/8 diameter and approx. 2" profile, uses a 3V Lithium Battery (CR123A) for long life
- Monitor alarms, restores, low battery, tamper and status
- Meets or exceeds codes: UL 2075, UL 2034

# **ZNAPCO** COMMERCIAL & GOVERNMENT SOLUTIONS



# Integrated Intrusion • Fire • Video • Access • Locking

- Innovative integrated enterprise class solutions reliable, high-quality security, life-safety, video, access and/or locking technologies integrated in one scalable interoperable platform called Napco Fusion<sup>™</sup>.
- Comprehensive Expert Support for endusers, architects and engineers, security consultants and commercial integrators
- Professional Tools, Training & Communications A growing list of the latest design support tools, CSI specifications, CAD diagrams and configuration aids are available on our website. Go to http://goo.gl/cbTdU An expert online support forum ensures continuous news and information is disseminated. Accredited training is provided in the field and in live and archived webinar modules online.
- Strong Security Heritage Napco Security Technologies, Inc. (NASDAQ: NSSC) has been solely dedicated to developing and manufacturing innovative professional security solutions since its founding in 1969.

- Industry-Leading Brands Napco Commercial<sup>™</sup> Gemini<sup>™</sup>, Continental CardAccess<sup>®</sup>, Alarm Lock Trilogy<sup>®</sup>, Networx<sup>™</sup>and Marks-USA<sup>™</sup>
- Commitment to Quality ISO9001:2000 Certified and subscribing to a rigorous quality management system, Napco products are precision-manufactured to meet or exceed industry specs.
- Built to Last Napco stands behind its products with among the longest warranties in the industry and even legacy systems are often field upgradable for lowest maintenance costs. Today, millions of people, businesses, institutions & residences around the world are protected by Napco products. Napco Security Systems & Peripherals are backed with a 36-month factory warranty.



Napco Security Technologies, Inc. (NASDAQ: NSSC) is ISO9001:2000 Certified and subscribes to a rigorous quality management system. Its products are precision manufactured to exceed industry standards, to be long lived and feature the lowest total cost of ownership. The Company includes some of the industry's best-known brands: Napco Security (encompassing Gemini, StarLink, Firewolf & iBridge), Continental Access, Alarm Lock and Marks USA, and their security solutions, such as, NapcoFusion<sup>™</sup> Interoperable Scalable Enterprise Securitiy Platform; CardAccess enterprise-class access systems; Trilogy standalone & wireless networked Networx PIN/Prox-ID access locks & new ArchiTech Networx customizable with over 300 trims and finishes; plus Lock-Down School Solutions, also from sister division Marks USA, respected for architectural, commercial & institutional locksets, including LocDown<sup>™</sup> Classroom Intruder Locksets & LifeSaver<sup>™</sup> door hardware for healthcare–all backed by Marks' Lifetime Mechanical Warranty.









www.alarmlock.com 1-800-ALA-LOCK salesinfo@alarmlock.com



www.continentalaccess.com 631-842-9400 salesinfo@cicaccess.com

MARKSUSA

www.marksusa.com 1-800-526-0233 salesinfo@marksusa.com

# Comparison of Gemini panel features & accessories

FEATURES GEMINI ALARM PANELS					
	GEM-P800	GEM-P801	GEM-P816	GEM-P1632	
ZONES ON BOARD	(acts as) 6	8	8	8	
MAX. # ZONES	6	9	16	32	
ZONE EXPANSION (NOTE: Each Custom Alpha Keypad adds 4 Built- in Zones) (2 on RP8LCD)	2 Wireless Only Zones	2 Wireless Only Zones	2xGEM-EZM4/8 1xGEM-EZM8	6xGEM-EZM4/8 3xGEM-EZM8	
USER CODES	8	8	16	32	
# OF FIRE ZONES; 2 WIRE FIRE	1 2/4 WIRE	1 2/4 WIRE	UP TO 16; 2 2-WIRE	UP TO 32; 2 2-WIRE	
KEYPADS OR USER INTERFACES SUPPORTED PLUS	4(total) GEM-RP8 RP8LCD or GEM-K800 IREMOTEMOD/12 (Note: iBridge Services NOT supported.)	4(total) GEM-RP8 RP8LCD or GEM-K800 IREMOTEMOD/12 (Note: iBridge Services NOT supported.)	7 (total) GEM-RPICAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS K3DGTL or DK1CA DK3DGTL, K4RF, K4 -PLUS- IREMOTEMOD/12; iBridge App or IBR-ITAB Touchscreen	7 (total) GEM-K1VPS, K1V, RP1CAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS K3DGTL or DK1CA DK3DGTL, K4RF, K4 -PLUS- IREMOTEMOD/12; iBridge App or IBR-ITAB Touchscreen	
CONTROL4 CERTIFIED INTEGRATION, SDDP & ETHERNET	NO	NO			
EVENT LOG	50	50	256	400	
# OF AREAS	1	1	1	2	
# OF OUTPUTS	2	2	3	3, UP TO 11 (Using RB3008 Relay Modules)	
# OF WIRELESS RECEIVERS SUPPORTED	2 (GEM-RECVXP8 only)	2 (GEM-RECVXP8 only)	2 (GEM-K4RF, RECV32)	2 (GEM-K4RF RECV32/96)	
# WIRELESS POINTS	8	8	16	32	
# WIRELESS KEYFOBS	4	4	8	8	
AUTO ARM	-	-	YES	YES	
OPEN/CLOSE SUPPRESSION	-	-	YES	YES	
AUTO DISARM	-	-	-	-	
SCHEDULES	-	-	-	-	
LINE CUT DETECT	YES	YES	YES	YES	
BELL SUPERVISION	YES	YES	YES	YES	
COMMUNICATION FORMATS	CONTACT ID; 4/2 & StarLink Cellular	CONTACT ID; 4/2 & StarLink Cellular	CONTACT ID; 4/2 & StarLink Cellular, SIA	CONTACT ID; 4/2 & StarLink Cellular, SIA	
INPUT POWER	16.5 VAC	16.5 VAC	16.5 VAC	16.5 VAC	
MAX STANDBY CURRENT	500mA	650mA	650mA	650mA	
ALARM CURRENT	2 AMPS	2 AMPS	2 AMPS	2 AMPS	
	GEM-P800 Control, Keypad & Transformer	GEM-P801 Control, RP8 Keypad & Transformer	GEM-P816 Control & Transformer.	GEM-P1632 Control & Transformer	
		GEM-P801ALPHA Control, Custom Alpha RP8LCD Keypad & Transformer	816PERFPAK Control, GEM-RP3DGTL Keypad, Transformer Also, K816PERFPAK, same but w/ GEMK3DGTL stay away style keypad		
AVALABLE IN THESE		801LCD-SUPERSVR Control, Custom Alpha RP8LCD Keypad, Siren, PIR1680PT, Jack, Cord, 4AH Battery & Transformer	816PERFPAKPLUS Control, GEM-RP3DGTL Keypad, Transformer, Siren, PIR, Jack, Cord, 4AH Battery Also, K816PERFPAK, same but w/ GEMK3DGTL stay/ away style keypad	GEM-K12OPAK Control, Fixed LCD Keypad w/ built in 32pt RF Receiver and stay/away style keys, Siren, PIR1680PT, Jack, Cord, 4AH Battery, Transf.	
CONFIGURATIONS		801KSUPERSAVER Control, K800 LED Keypad w/Stay/Away Keys, Siren, PIR1680PT, Jack, Cord, 4AH Battery & Transformer	816PREMPAK Control, GEM-RPICAe2 Keypad, Transformer Also, K816PREMPAK, same but w/ GEM-K1CA stay/away style keypad	1632INTROPAK Control, GEM-RPICAe2 Keypad, Transformer Also, K1632INTROPK, same but w/ GEM-K1CA stay/away style keypad	
		801SUPERSAVERPK as above but with RP8 LED Keypad with classic RP Keys		GEMP1632DK1WL Control, GEM-DK1CA Alpha Door Keypad, Xformer, Wireless GEM- PIRPET, 3ea.Low-Profile -TRANSLP, 32pt Receiver.	

GEMINI ALARM PANELS							
GEM-P1664	GEM-P3200	GEM-P9600	GEM-X255				
8	8	8	8				
64	32/48	96	255				
GEM-EZM4/8 GEM-EZM8	3xGEM-EZM8	3xGEM-EZM8 1xGEM-EZM8	GEM-EZM8 31xGEM-EZM8				
64	48	96	195				
UP TO 64; 2 2-WIRE	UP TO 32; 2 2-WIRE	UP TO 96 WITH UP TO 8 2-WIRE FIRE	UP TO 255 WITH UP TO 8 2-WIRE FIRE				
7 (total) GEM-K1VPS, K1V, RP1CAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS or DK1CA DK3DGTL, K3DGTL K4RF, K4 -PLUS- IREMOTEMOD/12; iBridge App or IBR-ITAB Touchscreen	7 (total) GEMRP1CAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS K3DGTL or DK1CA DK3DGTL, K4RF, K4 -PLUS- IREMOTEMOD/12; iBridge App or IBR-ITAB Touchscreen	15 (total) GEMRP1CAe2 RP2ASe2 RP3DGTL or GEM-K1CA K2AS K3DGTL or DK1CA DK3DGTL, K4RF, K4 -PLUS- IREMOTEMOD/12; iBridge App or IBR-ITAB Touchscreen	15 (total) GEM-RP1CAe2 GEM-K1CA GEM-DK1CA - <i>PLUS</i> - IREMOTEMOD/12; iBridge App or IBR-ITAB Touchscreen				
400	800	800	800				
4	2	8	8				
3 UP TO 16 (Using RB3008 Relay Modules)	3, UP TO 27 (Using RB3008 Relay Modules)	3, UP TO 99 (Using RB3008 Relay Modules)	3, UP TO 99 (Using RB3008 Relay Modules)				
2 (GEM-K4RF RECV32/96)	3 (GEM-K4RF RECV32/96)	4 (GEM-K4RF RECV32/96)	4 (RECV32/96/255)				
64	48	96	255				
8	8	16	16				
 YES	YES	YES	YES				
YES	YES	YES	YES				
-	YES	YES	YES				
-	255	255	255				
YES	YES	YES	YES				
YES	YES	YES	YES				
CONTACT ID; 4/2 & StarLink Cellular, SIA	CONTACT ID; 4/2 & StarLink Cellular, SIA, Modem II	CONTACT ID; 4/2 & StarLink Cellular, SIA, Modem II, (RS232 output option)	CONTACT ID; 4/2 & StarLink Cellular, SIA, Modem II, (RS232 output option)				
16.5VAC	16.5 VAC	16.5 VAC	16.5 VAC				
650mA	650mA	750mA	750mA				
2 AMPS	2 AMPS	2 AMPS	2 AMPS				
GEMP1664 Control & Transformer	GEM-P3200 Control & Transformer	GEM-P9600 Control & Transformer	GEM-X255 Control & Transformer				
GEMP1664VPSPK 4-area control, Multifunction LCD Coded Talking Keypad w/ built in UL siren, occupancy sensor and 25'Pet PIR (GEM- K1VPS); transf.	Optional Mercantile Housing, H1217 or w/ unit GEM-P3200M	Optional Mercantile Housing, H1217 or w/ unit GEM-P9600M					
GEMP1664DK1PK 4-area control, in oversized locking enclosure, Door-Style Keypad (GEM-DK1CA), transf.							

# Bridge Connected Home



#### **ABOUT NAPCO**

NAPCO Security Technologies, Inc. has a long heritage dedicated solely to developing innovative technology and reliable security solutions for the professional security community, including popular StarLink Universal Wireless GSM & CDMA Radios, NAPCO Commercial 24V Addressable/Conventional/Wireless Systems; Firewolf Fire Panels & Devices; iBridge Connected Home Remote Services with new iBridge Messenger SMS/MMS Notifications and Gemini intrusion and fire systems. NAPCO's many award-winning products are proven reliable, built to last, and proudly backed by the industry's longest warranty.





1-800-645-9445• www.napcosecurity.comNapco• Alarm Lock• Continental Access• Marks USA333 Bayview Avenue• Amityville, New York , U.S.A. 11701• Fax: 631-789-9292International ++ 1 631 842 9400NASDAQ: NSSCA402L



Napco Commercial, Firewolf, Gemini, iBridge, iBridge Messenger, iSeeVideo, iRemote, StarLink, NetLink, Napco Express, Quickloader, Adaptive, Trilogy, Networx, CardAccess, Napco Fusion, ArchiTech, LocDown & LiveSaver are trademarks of NAPCO. iPhone, iPad, Android, Z-Wave, Microsoft / Windows, Verizon, Control4, HID, & iClass are trademarks of their respective companies. Pats. & Pats. pending. Some preliminary specifications are subject to change. NAPCO Security Technologies, Inc. © NAPCO 2015.5