iSeeVideo Wireless IP Cameras: Let us show you how to become a part of the fastest growing, new source of RMR in the industry

Easy on you Affordable and valuable to them

Put video accounts online in minutes

One-button auto-secure function on Wireless Access Point (WAP) secures network

Patented auto-detect and enrollment of wireless cameras - true plug-n-play

New wireless cameras install in minutes –
Fixed or Pan and Tilt IP cameras available

25FPS high-res video (640x480)

View streaming video on any smartphone – iPhone and Blackberry.

FREE downloadable Blackberry app for full screen streaming, pan/tilt video in their hand

Put video accounts online in minutes with wireless cameras:

- Patented auto-detect and enrollment of wireless cameras- true plug-n-play
- One-button auto-secure function on Wireless Access Point (WAP) secures network
- Put video accounts online in minutes
- Highest resolution remote video on the market! 25 frames per second @ VGA res. (640x480)

Get more recurring monthly revenue from online video, more new accounts and reduce attrition

- Complete turnkey kits with no dealer buy-in programs
- Customers receive alerts via email
- 30 second post and pre event recording
- Part of Napco's total security solution, including alarm system integration, IVR-250 online video recorder and upcoming virtual online keypad
- Brand your own online customer access site, provided and hosted by iSeeVideo
- Works with any web enabled computer or smart phone
- Great iPhone experience - no app needed
- Free Blackberry app for client convenience and higher resolution

Highest resolution remote video delivered on the market!
25FPS @ VGA res.

NAPCO

Napco Security Technologies, Inc.
333 Bayview Avenue, Amityville, NY 11701
1.800.645.9445 • www.napcosecurity.com
Preliminary specifications subject to change.
© Napco, 3/2010

NAPCO ISEE-PTWLG Wireless Pan / Tilt IP Camera

Video Image Sensor: CMOS, 1/4" VGA Resolution
Lens: F2.0 Fixed Focus, Effective Range : 50cm to infinity
Compression: MPEG-4 / M-JPEG Dual Stream
Resolution Support: 640 x 480, 320 x 240, 160 x 120
Frame Rate: Up to 30 frame per second in VGA (640 x 480)
Image Control: AWB, AGC, Sharpness, Brightness
3GPP: 160 x 120 @ 15fs, MPEG-4 for mobile phone viewing

Pan/Tilt/Zoom

Pan Range: 126° (Left 63° ~ Right 63°) + 53° View Angle
Tilt Range: 64° (Up 28° ~ down 36°) + 53° View Angle
Preset Position: 10 Preset Positions, Support Patrol Mode
Digital Zoom: 4 x Digital Zoom

Audio

Microphone/Speaker: Bi-directional audio, built-in Mic and external Speaker

Software

Client Support: Fully Compatible with NAPCO iSeeVideo Server System
E-mail Notification: Triggered by motion detection
Users: 5 simultaneous users

Wireless

Standard: IEEE 802.11b, 802.11g and 802.11n
Range Indoor: 50m
Encryptions: WEP 64 Bits / 128 Bits, WPA / WPA2 Personal, WPS
Frequency: 2.4 ~ 2.4835GHz, DSSS
Antenna: 2dbi, Detachable
Enrollment: NAPCO Automatic Secure Enrollment (Patents Pending)

Hardware

CPU: SC1100 SOC with Hardware MPEG-4/ M-JPEG Codec
LAN: Ethernet 10 / 100BaseT
Power Adapter: 5V / 2A, 100 / 240 VAC
Certification: CE / FCC
Dimensions (HxWxD): 146 x 96 x 78 mm (5.7" x 3.8" x 3.1")
Weight: 318g (0.70lb.) without stand, 422g (0.93lb.) with stand
Working Temperature: -5 degree C to +50 degree C

NAPCO ISEE-VCWLG Wireless Fixed IP Camera

Video

Image Sensor: Ominivision 7725 CMOS, 1/6" VGA Resolution
Lens: F2.8Fixed Focus, Effective Range: 0.2M to infinity
Compression: MPEG-4/M-JPEG Dual Stream
Resolution Support: 640x480, 320x240, 160x120
Frame Rate: Up to 30 frames per second in VGA (640x480)
Image Control: AWB, Brightness
Video Options: Motion-Detection, Time Stamp, Text Overlay
3GPP: 160x120@15fs, MPEG-4 for mobile phone viewing

Audio

Microphone/Speaker: Bi-directional audio, built-in Mic and external Speaker

Software

Client Support: Fully Compatible with NAPCO iSeeVideo Server System
Users: 5 simultaneous users

Wireless

Standard: IEEE 802.11b, 802.11g and 802.11n
Range Indoor: 50m
Encryptions: WEP 64 Bits/128 Bits, WPA-PSK Personal, WPA2 Personal
Frequency: 2.4~2.4835GHz, DSSS
Antenna: 2dbi, Detachable
Enrollment: NAPCO Automatic Secure Enrollment (Patents Pending)

Hardware

CPU: SC1100 SOC with Hardware MPEG-4/M-JPEG Codec
LAN: Ethernet 10/100BaseT
Privacy Button: Privacy Button for video enable/disable
Power Adapter: 5V/1A, 100/240 VAC
Certification: CE/FCC
Dimensions (HxWxD): 96 x 90 x 36 mm
Weight: 131g (0.29lb.) without stand, 256g (0.56lb.) with stand
Operating Temperature: -5C ~ 50C

ISEE-WLAP: Wireless Access Point

• Allows automatic registration of wireless devices
• Secure lockdown upon system setup
• 802.11 B/G/N compatible
• Compact unit

ORDERING INFORMATION

PTWLG-KT/12 Wireless Pan/Tilt Camera Kit, includes: (1) ISEE-PTWLG indoor pan/tilt color wireless IP camera, 1/4" CMOS sensor, 802.11n, VGA res (640 x 480) at up to 25 fps, MPEG4 compression, with 2 way audio support, low lux operation, power adaptor w/ 15ft cable.   (1) ISEE-wlap wireless access point, 802.11b/g/n, with power supply and CAT5 cable, provides fast, secure one step deployment of wireless cameras (NAPCO patents pending) Includes 12 months of ISEEVideo network service

ISEE-PTWLG/12 Add-on Wireless Pan/Tilt Camera, as above, includes cables and 12 months of ISEEVideo network service

VCWLG-KT1/12 Wireless Fixed One Camera Kit, includes: (1) ISEE-VCWLG indoor fixed IP color wireless camera, 1/4" CMOS sensor, 802.11n, VGA res (640 x 480) at up to 25 fps, MPEG4 compression, with 2 way audio support, low lux operation, power adaptor w/ 15ft cable. Includes VCAM1-BKT1 suction cup bracket for window mounting (1) ISEE-wlap wireless access point, 802.11b/g/n, with power supply and CAT5 cable, provides fast, secure one step deployment of wireless cameras (NAPCO patents pending) Includes 12 months of ISEEVideo network service

ISEE-VCWLG/12 Add-on Fixed Camera, as above, includes cables and 12 months of ISEEVideo network service

ISEE-SCHGW Single Channel Gateway

ISEE-WLAP Wireless Access Point