FEATURES

- · 300 User codes: Master, manager, supervisor & basic users.
- · All Trilogy Mortise Lock Models are weatherproof and operate from -29 to 66 degrees C (-20 to 151 degrees F)
 - · Keypad- or Windows PC-Programmable.
 - Real time clock enables up programming of up to 500 scheduled events and holiday schedules.
 - 40,000 Event audit trail provides a printed time/date- stamped log of all electronic activity. · Audit Trail at handheld infrared printer, PC or Data Transfer Module.
 - · Standalone access control system with long-life batteries and low battery alert.
- · Exceptionally durable clutch mechanism
- . 'Ouick Passage' Mode enabled with any authorized user code and function code
- · 4-Hour Fire Rated

ADVANCED "SMART" APPLICATIONS

Scheduled Events: Program to lock/unlock: disable/enable users: relay control. Audit Trail with Time/Date Stamp: Provides a printable record of all electronic activity. including. Unlock/lock events, program mode changes, user entry, keypad lockout, remote release events, unauthorized code attempts, etc.

- · 4 Programming levels
- · 4 User erouns
- 3 to 6 Digit Codes Onestime service code
- Total user lockout mode
- . 'First-Manager-In' feature set
- Tri-coloured LED indicator indicates code accentance or denial (green or red, respectively). or low battery condition (vellow).
- · Non-volatile memory of both programming and audit trail activity
- · Keypad tamper lockout
- · Programmable Form C Relay functions for scheduled or keypad-activated control of CCTV, lighting, ambush function, alarm system, etc.

SPECIFICATIONS

Operation: Authorized digital code enables lever to retract latchbolt from outside. Inside lever is always in passage mode and retracts latchholt. Deadholt is operated by key cylinder only from either side

Operating Temperature: Weatherproof lock operating range from -29 to 66 degrees C (-20 to 151 degrees F) Keypad: Weatherproof, 12-button, metal is vandal, resistant

Programming: Locking modes, codes, and allowable entry time (3, 10 or 15 seconds), etc. can be programmed at the keypad, the Data Transfer Module (AL-DTM) or using any PC running Alarm Lock DL-Windows Software

Audit Trail: Locks' entry activity log can be downloaded to the Data Transfer Module (AL-DTM), any PC using DL-Windows Software, or can be on-site printed using the hand-held infrared printer (AL-IR1). Power: 5AA alkaline batteries, furnished,

Audible and visual low battery alert, and entry indicators, up to 80,000 cycles, typical. Cylinder: Uses standard European profile cylinder. not supplied. For 45mm thick doors use 85mm long cdinder Door Thickness: Standard 45mm(1½") thickness.

(Usable on doors up to 35 to 47mm (15%" to 17%")). Backset: (Omm Case Deoth: 88mm

Lock Centres: 72mm

Strike: Stainless steel straight lip strike supplied, for use on both left and right handed doors. (36.5 x 1280mm). Trim: Non-handed, fully reversible, tubular lever handle Handing: Left (L) or Right (R) Handed Models must be specified upon ordering. Latch and strike are fully reversible.

Finishes: US26D Satin Chrome standard. Other finishes special ordered including: US5 Antique Brass, US3 Polished Brass, US26 Polished Chrome

Compliances: CE. 4-Hour Fire Rated



